

FILE
1983

SJT 100/200/300

SelectaVision® VideoDisc System CED Basic Service Data

RCA Corporation Consumer Electronics

Technical Publications
P.O. Box 1976 | Indianapolis, Indiana 46206

RCA Inc.


Technical Publications

5575 Royalmount Avenue | Town of Mount-Royal | Quebec, Canada H4P 1J8

Canada Stock Numbers:

Add prefix 62 to all stock numbers.

Model SJT 100/ 101/200/300



SJT 200

TO AVOID ERROR file all supplements and addendums as soon as received. Consult these before ordering parts.

Service Data Contents

	PAGE
Adjustments	
Electrical	23 thru 26
Mechanical	16
Circuit Boards	
PW 400 Arm Preamp	56
PW 600 AC Input	56
PW 900 Remote I/R Preamp	56
PW 1000 Remote I/R Transmitter	54
PW 1100 Remote Decoder	54
PW 1700 Display	56
PW Arm Interconnect	56
PW Master	51, 52, 53
Circuit Protection	6
Critical Copper Pattern	9
Component Numbering System	8
Electrical Adjustment Location Guide	37
Electronic Systems Description	14, 15, 16
Exploded Views	
Arm Assembly—SJT 100/200	63
Arm Assembly—SJT 300	63
Arm Drive Assembly	63
Cabinet and Mechanism	60, 61, 62
Frequently Used Abbreviations	9
Functional Block Diagram	57, 58, 59
General Information	7
Glossary	10
Integrated Circuit Block Diagrams	38
Instrument Disassembly	17 thru 22
Instrument Shipping	8
Interconnect Wiring Diagram	39, 40
Mechanical Operation	12, 13
Operating Controls & Functions	6
Replacement Parts	64 thru 70
Safety Precautions	2
Schematics	
Audio—Monaural	50
Audio—Stereo	48, 49
Pickup Arm	41
Player Control	42, 43, 44
Power Supply	50
Remote Preamp/Decoder	55
Remote Transmitter CRK34	54
Signal Processing	45, 46, 47
Service Alignment Disc Contents	11
Servicing Precautions	3, 4
Specifications	5
Test Point and Active Device Location Chart	32
Test Point and Active Device Identification	33
Turntable Height Adjust	16
Voltage Charts	
Integrated Circuits	26 thru 29
Transistors	30, 31
Waveforms	34, 35, 36

**CAUTION: DO NOT USE MONAURAL ALIGNMENT (TEST) DISC STK. NO.
149235 WITH MODELS COVERED BY THIS SERVICE DATA.**

NOTE: MODEL SJT 101 IS ELECTRONICALLY AND MECHANICALLY THE SAME AS MODEL SJT 100.


SAFETY NOTICE

Components having special safety characteristics are identified by shading on schematics and by * stars on the parts list in this Service Data and its supplements and bulletins. Before servicing this instrument, it is important that the service technician read and follow the "Safety Precautions" and "Product Safety Notices" in this Service Data.

SAFETY PRECAUTIONS

1. Before returning the VideoDisc Player to the customer, always make a safety check of the entire instrument, including, but not limited to, the following items:
 - a. Be sure that no built-in protective devices are defective and/or have been defeated during servicing. (1) Protective shields are provided on this VideoDisc Player to protect both the technician and the customer. Correctly replace all missing protective shields, including any removed for servicing convenience. (2) When reassembling the VideoDisc Player, be sure to put back in place all protective devices, including, but not limited to, non-metallic control knobs, insulating fishpapers, adjustment and compartment covers/shields, and isolation resistor/capacitor networks. **Do not operate this instrument or permit it to be operated without all protective devices correctly installed and functioning. Servicers who defeat safety features or fail to perform safety checks may be liable for any resulting damage.**
 - b. Be sure that there are no cabinet openings through which an adult or child might be able to insert their fingers and contact a hazardous voltage. Such openings include, but are not limited to, (1) excessively wide cabinet ventilation slots, and (2) improperly fitted and/or incorrectly secured cabinet covers.

- c. **Leakage Cold Check** — With the VideoDisc Player AC plug removed from any AC source, connect an electrical jumper across the two AC plug prongs. Place the VideoDisc Player AC switch in the **on** position. Connect one lead of an ohmmeter to the AC plug prongs tied together and touch the other ohmmeter lead in turn to each push button/customer control, exposed metal screws, metalized overlays and to each cable connector. If the measured resistance is less than 1.0 megohm or greater than 5.2 megohm (except for the center conductor of the F connector that feeds the TV receiver which will measure **open** when the function switch is in the play position) an abnormality exists that must be corrected before the VideoDisc Player is returned to the customer. Repeat this test with the VideoDisc Player AC switch in the **off** position. All the preceding tests should be made with a Disc in the player and repeated **without a Disc** in the player.



AC Leakage Test

d. **Leakage Current Hot Checks**

On completely assembled instrument, with a Disc in the Player and all tests repeated without a Disc in the Player, plug the AC line cord directly into a 120V AC outlet. (Do not use an isolation transformer during this test.) Use a leakage current tester or a metering system that complies with American National Standards Institute (ANSI) C101.1 *Leakage Current for Appliances* and Underwriters Laboratories (UL) 1410, (50.7). Measure for current, with the

player in the *play* position and repeat with the player in the *Load-Unload* and *off* positions from a known earth ground (metal waterpipe, conduit, etc.) to all exposed metal or conductive parts of the instrument (antenna connections, handle bracket, metal cabinet, screwheads, metallic overlays, push-buttons, control shafts, etc.), especially any exposed metal parts that offer an electrical return path to the Player deck. Any current measured must not exceed 0.5 milliamp. Reverse the instrument power cord plug in the outlet and repeat test.

ANY MEASUREMENTS NOT WITHIN THE LIMITS SPECIFIED HEREIN INDICATE A POTENTIAL SHOCK HAZARD THAT MUST BE ELIMINATED BEFORE RETURNING THE INSTRUMENT TO THE CUSTOMER OR BEFORE CONNECTING TO AN ANTENNA OR ACCESSORIES.

e. **Interconnected Equipment AC Leakage Test**

Avoid shock hazards. The television instrument, accessory, or cable(s) to which this VideoDisc Player is connected should have the applicable sections of the leakage resistance cold check and the leakage current hot check performed. Do not connect this VideoDisc Player to a TV antenna, cable or accessory that exhibits excessive leakage currents.

2. Read and comply with all caution and safety-related notes on or inside the VideoDisc Player cabinet, and on the Player deck.

3. **Design Alteration Warning** — Do not alter or add to the mechanical or electrical design of this VideoDisc Player. Design alterations and additions, including, but not limited to, circuit modifications and the addition of items such as auxiliary audio and/or video output connections, cables and accessories etc. might alter the safety characteristics of this VideoDisc Player and create a hazard to the user. Any design alterations or additions may void the manufacturer's warranty and may make you, the servicer responsible for personal injury or property damage resulting therefrom.

4. Observe original lead dress. Take extra care to assure correct lead dress in the following areas: a. near sharp edges, b. near thermally hot parts — be sure that leads and components do not touch thermally hot parts in the AC and DC supplies. Always inspect in all areas for pinched, out-of-place, or frayed wiring. Do not change spacing between components, and between components and the printed-circuit board. Check AC power cord for damage.

5. Components, parts, and/or wiring that appear to have overheated or are otherwise damaged should be replaced with components, parts, or wiring that meet original specifications. Additionally, determine the cause of overheating and/or damage and, if necessary, take corrective action to remove any potential safety hazard.

6. **PRODUCT SAFETY NOTICE** — Many electrical and mechanical parts have special safety-related characteristics some of which are often not evident from visual inspection, nor can the protection they give necessarily be obtained by replacing them with components rated for higher voltage, wattage, etc. Parts that have special safety characteristics are identified in RCA service data by *shading* on schematics and by a (*) in the parts list. Use of a substitute replacement that does not have the same safety characteristics as the recommended replacement part in RCA service data parts list might create shock, fire, and/or other hazards. Product Safety is under review continuously and new instructions are issued whenever appropriate. For the latest information, always consult the appropriate current RCA service literature. A subscription to, or additional copies of, RCA service literature may be obtained at a nominal charge from your RCA Consumer Electronics Distributor or from RCA Technical Publications, P.O. Box 1976, Indianapolis, IN 46206, or Canadian residents may order from RCA Inc., Technical Publications, 5575 Royalmount Ave., Town of Mount-Royal, Quebec H4P 1J8 Canada.

SERVICING PRECAUTIONS

4. Use only an *anti-static* type solder removal device. Some solder removal devices not classified as "anti-static" can generate electrical charges sufficient to damage ES devices.
5. Do not use freon-propelled chemicals. These can generate electrical charges sufficient to damage ES devices.
6. Do not remove a replacement ES device from its protective package until immediately before you are ready to install it. (Most replacement ES devices are packaged with leads electrically shorted together by conductive foam, aluminum foil or comparable conductive material.)
7. Immediately before removing the protective material from the leads of a replacement ES device, touch the protective material to the instrument ground or circuit assembly into which the device will be installed. **CAUTION:** Be sure no power is applied to the instrument or circuit, and observe all other safety precautions.
8. Minimize bodily motions when handling unpackaged replacement ES devices. (Otherwise harmless motion such as the brushing together of your clothes fabric or the lifting of your foot from a carpeted floor can generate static electricity sufficient to damage an ES device.)

General Soldering Guidelines

1. Use a grounded-tip, low-wattage soldering iron and appropriate tip size and shape that will maintain tip temperature within the range 500°F to 600°F.
2. Use an appropriate gauge of RMA resin-core solder composed of 60 parts tin/40 parts lead.
3. Keep the soldering iron tip clean and well tinned.
4. Thoroughly clean the surfaces to be soldered. Use a small wire-bristle (0.5 inch, or 1.25 cm) brush with a metal handle. Do not use freon-propelled spray-on cleaners.
5. Use the following unsoldering technique:
 - a. Allow the soldering iron tip to reach normal temperature (500°F to 600°F).
 - b. Heat the component lead until the solder melts.
 - c. Quickly draw away the melted solder with an anti-static, suction-type solder removal device or with solder braid.

CAUTION: Work quickly to avoid overheating the circuit board printed foil.

6. Use the following soldering technique:
 - a. Allow the soldering iron tip to reach normal temperature (500°F to 600°F).
 - b. First, hold the soldering iron tip and solder strand against the component lead until the solder melts.
 - c. Quickly move the soldering iron tip to the junction of the component lead and the printed circuit foil, and hold it there only until the solder flows onto and around both the component lead and the foil.

CAUTION: Work quickly to avoid overheating the circuit board printed foil.

- d. Closely inspect the solder area and remove any excess or splashed solder with a small wire-bristle brush.

IC Removal/Replacement

Use the following technique for IC removal and replacement.

Removal

1. Desolder and draw away the melted solder with an anti-static suction-type solder removal device (or with solder braid) before removing the IC.

SERVICING PRECAUTIONS

Replacement

- Carefully insert the replacement IC in the circuit board.
- Carefully bend each IC lead against the circuit foil pad and solder it.
- Clean the soldered areas with a small wire-bristle brush. (It is not necessary to reapply acrylic coating to the areas.)

"Small-Signal" Discrete Transistor Removal/Replacement

- Remove the defective transistor by clipping its leads as close as possible to the component body.
- Bend into a "U" shape the end of each of three leads remaining on the circuit board.
- Bend into a "U" shape the replacement transistor leads.
- Connect the replacement transistor leads to the corresponding leads extending from the circuit board and crimp the "U" with long nose pliers to insure metal to metal contact, then solder each connection.

Power Output Transistor Devices Removal/Replacement

- Heat and remove all solder from around the transistor leads.
- Remove the heatsink mounting screw (if so equipped).
- Carefully remove the transistor from the circuit board.
- Insert new transistor in circuit board.
- Solder each transistor lead, and clip off excess lead.
- Replace heatsink.

Diode Removal/Replacement

- Remove defective diode by clipping its leads as close as possible to diode body.
- Bend the two remaining leads perpendicularly to the circuit board.
- Observing diode polarity, wrap each lead of the new diode around the corresponding lead on the circuit board.
- Securely crimp each connection and solder it.
- Inspect (on the circuit board copper side) the solder joints of the two "original" leads. If they are not shiny, reheat them and, if necessary, apply additional solder.

Fuse and Conventional Resistor Removal/Replacement

- Clip each fuse or resistor lead at top of circuit board hollow stake.
- Securely crimp leads of replacement component around notch at stake top.
- Solder the connections.

CAUTION: Maintain original spacing between the replaced component and adjacent components and the circuit board, to prevent excessive component temperatures.

Circuit Board Foil Repair

Excessive heat applied to the copper foil of any printed circuit board will weaken the adhesive that bonds the foil to the circuit board, causing the foil to separate from, or "lift-off", the board. The following guidelines and procedures should be followed whenever this condition is encountered.

In Critical Copper Pattern Areas


High component/copper pattern density and/or special voltage/current characteristics make the spacing and integrity of copper pattern in some circuit board areas more critical than in others. The circuit foil in these areas is designated as *Critical Copper Pattern* and is identified and illustrated in this service data in the section titled *Safety Related Copper Pattern* (see table of contents for page number). Because Critical Copper Pattern requires special soldering techniques to ensure the maintenance of reliability and safety standards, contact your local RCA Consumer

Electronics Distributor Service Manager before attempting repair of Critical Copper Pattern.

At IC Connections

To repair defective copper pattern at IC connections, use the following procedure to install a jumper wire on the copper pattern side of the circuit board. (Use this technique only on IC connections.)

- Carefully remove the damaged copper pattern with a sharp knife. (Remove only as much copper as absolutely necessary.)
- Carefully scratch away the solder resist and acrylic coating (if used) from the end of the remaining copper pattern.




Install Jumper Wire and Solder

- Bend a small "U" in one end of a small-gauge jumper wire and carefully crimp it around the IC pin. Solder the IC connection.
- Route the jumper wire along the path of the cut-away copper pattern and let it overlap the previously scraped end of the good copper pattern. Solder the overlapped area, and clip off any excess jumper wire.

At Other Connections

Use the following techniques to repair defective copper pattern at connections other than IC Pins. This technique involves the installation of a jumper wire on the component side of the circuit board.

- Remove the defective copper pattern with a sharp knife. Remove at least 1/4 inch of copper, to ensure that a hazardous condition will not exist if the jumper wire opens.
- Trace along the copper pattern from both sides of the pattern break and locate the nearest component that is directly connected to the affected copper pattern.
- Connect insulated 20-gauge jumper wire from the lead of the nearest component on one side of the pattern break to the lead of the nearest component on the other side. Carefully crimp and solder the connections.



Insulated Jumper Wire

CAUTION: Be sure the insulated jumper wire is dressed so that it does not touch components or sharp edges.
F013.4.2

SPECIFICATIONS

Power Input: — 120 VOLTS, 50/60 Hz.

Power Consumption: — SJT 100 — 25 WATTS
SJT 200 — 27 WATTS
SJT 300 — 28 WATTS

Antenna Impedance: — 75 ohm in/out

RF Output Level: — 3 mV Maximum
1 mV Minimum
Switchable to
Channel 3 or 4

Circuit Boards: — PW 200 — RESONATOR
PW 400 — Arm Preamp
PW 600 — AC input
PW 900 — Remote IR Preamp
PW 1100 — Remote Amp
PW 1700 — Display
PW 5600 — Function Switch Assembly
PW Hook up-Pickup Arm

Interconnect
PW Master — Master Circuit Board

Weight: — Approx. 20 lbs.

Dimensions: — WIDTH — 17" (431.8 mm)
DEPTH — 16-1/2" (418.9 mm)
HEIGHT: — 5" (126.7 mm)

Turntable Speed: — 449.55 RPM Direct Drive
Quartz-Locked

Play Time: — 2 hours (1 hour per disc side)

Video Signal System: — EIA Standard NTSC Color
Signal

Video Output: — 1V p-p into 75-ohm termination 2V p-p
unterminated

Audio Output: — 2 channel 200 mV ± 20 mV RMS, into
10K ohm or greater impedance

Disc Play System: — CED Capacitance
Electronic Disc




Fig. 1—SJT 200 Operating Controls




Fig. 2—SJT 200 Rear Panel Connections

OPERATING CONTROLS AND FUNCTIONS

Power On/Off — Load — Play — Unload

Power is applied to the player by depressing the player on/off button. The player automatically places itself in the "Load" position (caddy entry door open). The digital readout indicator lights and displays a flashing "L".

To load player, insert loaded caddy into player gently until the player loading mechanism takes hold and pulls caddy into player (DO NOT force caddy into Player). When the caddy spine is latched the loading mechanism will reverse and return the empty sleeve (caddy) out beyond the caddy entry door opening. Remove the empty sleeve (caddy) from the player and the player will automatically place itself in the "Play" mode. During the automatic cycle the digital readout will display $\text{--}\bullet\text{--}$. In approximately 10 seconds a picture will appear on the TV screen and the digital readout will begin to display elapsed playing time in minutes.

When "Play" is completed (approximately 60 minutes) the digital readout will display a flashing "E" momentarily then the "E" lights continuously. In approximately 8 to 10 seconds the player automatically places itself in the "Unload" mode. The digital readout will display a flashing "UL" and the caddy entry door will open. Insert empty sleeve (caddy), in same manner prescribed for load procedure, to retrieve the disc and spine from the player. Remove loaded caddy from player and the digital readout will then begin displaying a flashing "L".

Audio A/B Button (Models SJT 200/300)

This function is active only when playing a special DUAL sound track or BILINGUAL disc. Press to select either the primary sound track "A" or the secondary sound track "B". Depending upon which sound track is active, the corresponding LED display lamp will light. (A/B).

NOTE: The player automatically selects the proper audio playback mode whether you are playing a special dual sound track, Bilingual, Stereo or monoral VideoDisc

Visual Search

Pressing either *Visual Search* Button, Fwd ▶ or Rev. ◀, (with disc in player) permits faster than normal (16 times

CIRCUIT PROTECTION

Fuse (or Device) F601

Circuit Protected
AC input

Physical Location
PW 600

normal speed) movement of the pick-up arm assembly. The stylus remains in contact with the disc permitting *Visual Search* (scan) viewing of the program material (audio is muted during this mode of operation).

Rapid Access (SJT 100/200)

Pressing either *Rapid Access* Button, Fwd ▶▶ or Rev. ◀◀ (Player must be in "Play" mode with disc in player) provides rapid movement of the pick-up arm assembly in direction selected. The Stylus lifter circuit is active in this mode of operation therefore the stylus is not in contact with the disc. (Video blanked, Audio muted).

Hi-Speed Scan (SJT300)

Pressing either *Hi-Speed Scan* Button, Fwd ▶▶ or Rev. ◀◀ (with disc in player) permits rapid (120 times normal speed) movement of the pick-up arm Assembly. The stylus remains in contact with the disc permitting hi-speed scan (search) viewing of the program material (Audio is muted during this mode of operation).

Pause/Play

Pressing the "Pause" Button (with disc in player) places the stylus lifter circuit into operation raising the stylus off the disc. Video is blanked, audio is muted, and there is no movement of the pick-up arm assembly in this mode of operation. The digital readout will display a flashing "P". Pressing the "Pause" button a second time returns the player to normal operation.

NOTE: For Model SJT 300 the in arm stylus cleaner (sweeper) is activated in the "Pause" mode.

Stereo Sound (SJT 200/300)

By connecting an external stereo amplifier (optional equipment) to the stereo output jacks on the back of the player you can enjoy stereo sound when playing a stereo disc.

Video Out Jack (Models SJT 200/300)

The video output jack (located on the back of the player) makes it possible to connect video from the player directly to a TV set or monitor equipped with a video input jack.

GENERAL INFORMATION

NOTE: Technicians servicing this product will find helpful the following related **RCA Technical Training Publications**.

VideoDisc Manual SJT200/300-1

This publication may be ordered, for a nominal charge, from: RCA Technical Publications 1-450, P.O. Box 1976, Indianapolis, IN 46206.

The New RCA SelectaVision VideoDisc Player is simple to operate, and easy to install. External connections to and from the player are minimal, involving only intercept and reconnection of the television VHF antenna input lead (cable). Necessary connecting lead (cable) and matching transformers are included to handle all but unusual installations.

1. A 5 foot, 75 ohm coaxial cable connects from the antenna out connector on the player, to the VHF antenna input on the television receiver. Use cable direct if the television has 75 ohm VHF antenna input connector; use via a 75 to 300 ohm matching transformer/adaptor if the television VHF antenna input is 300 ohm.
2. A 300 to 75 ohm matching transformer/adaptor mates a 300 ohm twin lead antenna system (outside or rabbit ears) to the player 75 ohm antenna input system. (Captive, screw type lugs are integral to the 300 to 75 ohm antenna matching transformer/adaptor; strip and insert the 300 ohm twin lead wires then tighten the screws.) Keep in mind — for different or "odd" antenna systems — the antenna input and output of the VideoDisc Player is 75 ohm unbalanced.

Antenna connection instructions should be carefully followed. The player produces an R-F signal which is transmitted on VHF Channel 3 or 4 (switch selectable) frequency. If the player antenna output is connected to an antenna, directly or in parallel from the television antenna input connections, the player may broadcast a signal. Broadcasting an unauthorized signal could violate certain regulations of the Federal Communications Commission regarding the operation of R-F devices. Recheck the installation to avoid any broadcasting possibilities; make sure the 75 ohm shielded cable is used to connect the R-F output of the player to the television receiver, and that no other connections are paralleled from these terminals.

The physical location of the antenna "in" and "out" connectors are depicted in the rear apron photo of the VideoDisc Player (Fig. 2). "F" type connectors accept the VHF antenna input and output cables.

Interface of the antenna system, VideoDisc Player, and monitor television receiver is controlled by an electronic antenna switch in the player. When the Player ON/OFF Switch is in the "OFF" position, the antenna is connected directly (via the player electronic antenna switch) to the television receiver and the television will operate normally. When the player ON/OFF switch is in the "ON" position, the antenna is disconnected and the player R-F output is connected directly to the television VHF antenna input connector. Under this condition the television receiver will receive a signal only on Channels 3 or 4 (switch selectable on the rear of VideoDisc Player Fig. 2). Specifically the VideoDisc Player antenna switch system serves to either connect the antenna system direct to the television VHF antenna input or disconnect the antenna system and connect the VideoDisc Player R-F output direct to the television VHF antenna connector.

Stereo output jacks are available (Models SJT 200/300) for connecting (cable included) stereo sound output to an external Stereo Amplifier (optional equipment). Also available is a Video Output Jack (Models SJT 200/300) for connecting (cable not included) a video signal directly to a television receiver or video monitor equipped with video input capabilities.

The new design of the RCA VideoDisc player uses the single-main circuit board concept. The main circuit board contains nearly all of the electronic circuits. Circuits not contained on the main circuit board are AC input, resonator, pick-up arm preamp, and in the case of the remote controlled VideoDisc player, the remote preamp and remote amplifier circuits.

Servicability of the new VideoDisc player is enhanced by the logical physical arrangement of circuits on the main circuit board. The board is segmented by **circuit area**. AND FURTHER ENHANCED BY PROMINENT ROAD MAPPING ON THE CIRCUIT BOARD. In addition, a component numbering system is used which relates to general circuit areas and will aid in readily locating individual components.

COMPONENT NUMBERING SYSTEM

Circuits not located on the Main Circuit Board and their numerical designation.

Component Numbering Versus Circuits.

0 - 99 — Mechanism/Player mounted components
100 series — PW Hookup on Arm assembly
200 series — Resonator on Arm assembly
400 series — Arm Preamp on Arm assembly
600 series — AC input
900 series — IR preamp (used SJT 300)
1100 series — Remote Receiver (Used SJT 300)
1700 series — Display board assembly
5600 series — Function Switch assembly

Circuits located on the Main Circuit Board and their numerical designation.

Component Numbering Versus Circuits

2000 series — Power Supply
2500 series — Pulse Interference Corrector (PIC)


2700 series — Video Output
3100 series — Non-Linear Aperture Correction (NLAC), Sound Beat Correction
3200 series — Video Demodulation
3300 series — Comb Filter/Defect Corrector
3400 series — Video Converter and Time Base Correction
3500 series — RF Modulator
4100 series — Audio Modulator
4200 series — Audio Track/Hold Mute (CMOS switch)
4300 series — Audio Matrix and Buffer (not used SJT 100)
4400 series — Audio Decoder Rectifier (not used SJT 100)
4500 series — Audio Decoder Control (not used SJT 100)
4600 series — Audio Output (not used SJT 100)
5100 series — Player Control
5300 series — Kicker Pulse
5900 series — Mechanism Control

INSTRUMENT SHIPPING


The customer instruction book advises the customer to retain the shipping tabs, original carton and packing material for use should they need to repack the player for moving or shipping.

To reinstall the shipping tabs for moving or shipping:

1. Be certain player is in "OFF" mode (caddy entry door closed).
2. Disconnect player from AC power and remove antenna Connections.
3. Replace shipping tabs (see illustrations).
4. Repack player in original carton for shipping using original packing material.
5. Be certain to include player accessories (antenna hook-up cable and adaptors, stereo hook-up cables — SJT 200/300 and Remote transmitter—SJT 300) if instrument is being returned for service.



Shipping Tabs—Removal



Shipping Tabs—Installation

Preparing The Player For Out-of-Carton Transport

When transporting the player out of original packing material, the following guidelines are recommended.

1. Be certain player is in "OFF" mode (caddy entry door closed).
2. Disconnect player from AC power source and remove antenna connections.
3. Replace shipping tabs (see illustrations).
4. Player can now be transported safely.

FREQUENTLY USED ABBREVIATIONS

AM	Audio Modulation
AMA	Audio Mute Primary Channel A
AMB	Audio Mute Secondary Channel B
ANX	Antenna Transfer
AO	Arm Output
AS	Arm Stretcher
CAB	Channel A/B
CO	Clock Output (or Chroma Output)
CR	Caddy Reverse
CS	Caddy Sense
CV	Control Voltage
CY	Cored Luminance
DD	Decoder Defeat
DG	Defect Gate
DS	Display
FM	Function Motor (or Frequency Modulation)
GND	Ground
HE	Hall Effect
HNC	Home Normally Closed
HNO	Home Normally Open
Hz	Hertz
IC	Integrated Circuit
KPO	Kicker Pulse Output
LA	Landing
LED	Light Emitting Diode
LO	Load
LSE	Least Significant Digit Voltage
MA	Modulator Audio
MSE	Most Significant Digit Voltage

SAFETY RELATED COPPER PATTERN

Modern circuit design/manufacturing techniques dictate a rather high component density on the printed circuit board utilized in this instrument. It naturally follows that the area available for "printing" copper patterns is also restricted. To maintain high reliability and safety standards, the printed circuit boards are manufactured under carefully controlled conditions and to extremely close tolerances. Some areas of the board are more critical than others due to spacing, pattern size, voltage/current requirements, etc. RCA has concluded, as a result of extensive studies that less-than-optimum repair of copper

patterns in these specific areas can degrade the reliability/safety of the instrument. The critical copper patterns are shown as "dark black" in the illustration (Fig. 3). In the event printed circuit damage is evident in these designated areas (copper pattern broken, lifted, etc.) special soldering techniques are necessary to maintain reliability and safety standards. Contact your local RCA Consumer Electronics Distributor Service Manager before attempting copper pattern repair in the designated areas on the board layout.




Fig. 3—PW 600 Critical Copper Pattern

GLOSSARY

Analog — Of or pertaining to the general class of devices or circuits in which the output varies as a continuous function of the input.

Angstrom — One tenth of a millimicron. Angstrom unit is a term utilized to express the length of very short waves.

Beats — A term used to describe the unwanted signals produced when two original signals are mixed together.

Buried Subcarrier — See Subcarrier, except frequency is down converted. Example: In CED system color burst is 1.53 MHz.

Burst — A short time occurrence (8 to 10 Hz) of the color subcarrier signal appearing right after Horizontal sync, but centered on the blanking portion of the video waveform.

Caddy — Name given to device in which the VideoDisc is enclosed (see sleeve).

Chroma — The color portion of a video signal.

D Flip-Flop — A dual solid state processing circuit, the output of which is determined by the input.

DAXI — Digital Auxiliary Information recorded on the disc and utilized by the player control microcomputer to control operation of the disc player.

Delta Frequency (Δf) — A term to indicate that a signal or frequency has some variation or change.

Dropout — A momentary absence of carrier signal off the disc, whether due to uneven stamping or a particle of dust on the disc or stylus.

Deviation — A term used to describe how far the FM carrier frequency swings when it is modulated.

Digital — Of or pertaining to the class of devices or circuits in which the output varies in discrete steps (i.e., pulses or "ON-OFF" operation).

Emphasis — The process of boosting the level of the high frequency portions of the video signal.

FM Signal — Abbreviation for Frequency Modulated Signal.

Field — One half of a television picture. A field consists of 262.5 horizontal scanning lines across a picture tube. Two fields (line 1 thru 252.5 and line 252.5 thru 525 interlaced) are necessary to complete a fully scanned television picture (frame). The two sweeps of the TV picture tube, or two fields make up one complete TV picture or "frame". Frame repetition is 30 Hz, therefore field repetition is 60 Hz.

Frame — One complete television picture (see "Field").

Gate — A circuit which will deliver an output only when a specific combination of its inputs are present for use in analog or digital applications.

Integrated Circuit (IC) — An electronic device in which both active and passive elements are contained in a single package.

Interlacing — The property of the scan lines of two television fields to lie in-between each other.

Interleaving — A term used to indicate that the harmonics of the chrominance signal lie in-between the harmonics of the luminance portion of the video signal as it is viewed on a spectrum analyzer. This means that the color information of a video signal

does not interfere with, although it is broadcast at the same time as, the luminance information.

Jitter — The name of an effect on the playback picture (sometimes referred to as "Wiggles" or "Flutter"). The picture appears to have a rapid shaking motion.

Luminance — This is the portion of the video signal which contains B/W information and sync (see "Y" signal).

Micro Computer — (μ C) A compact and inexpensive computer relatively limited in capability and capacity, consisting of a microprocessor and other components of a computer, commonly used to store and process digital information.

Micron — One millionth part of a meter.

Microprocessor — (μ P) — A miniaturized integrated circuit device which performs all of the functions of a central processing unit.

NLAC — Non Linear Aperture Correction — System which compensates for non-linear response of the stylus to the disc information.

NTSC — (National Television Systems Committee) — These four letters identify the United States Color Television Standard.

PIC — Pulse Interference Corrector—Circuit which detects and compensates for interference generated in the 900 MHz frequency range.

Resonator — A circuit that responds in accordance to oscillations produced in another circuit.

Sample and Hold (S/H) — A process by which the value of a particular signal is measured at a specific moment in time — then this signal is stored for later use.

Servo — Short for Servomechanism. An electromechanical device whose mechanical operation (for instance, motor speed) is constantly being measured and regulated so that it closely matches or follows an external reference.

Sleeve — Another name applied to the caddy in which the VideoDisc is enclosed. (See Caddy).

Spine — Device utilized in conjunction with the VideoDisc and caddy to support the disc when it is transferred from the caddy to the player.

Stylus — Diamond tipped device utilized to transfer video and audio information from disc to pickup arm assembly electronics.

Subcarrier — A carrier signal inserted within the passband of a broadcast signal to provide a channel for the transmission of additional information. Example: In color TV, the 3.58 MHz color burst.

VCO — (Voltage Controlled Oscillator) An oscillator whose frequency of oscillation is governed by an external voltage and/or timing capacitor in IC applications.

VCXO — (Voltage Controlled Crystal Oscillator) Similar to VCO except that a quartz crystal is used as a reference.

XTAL — Abbreviation for Crystal.

STEREO/MONO SERVICE ALIGNMENT DISC CONTENT

Segment	Time Display (Minutes)	Video Display	On Screen Display	Audio**	Daxl Band	Audio Code	Service Application
A	*	Grey Field		S1: Unmodulated S2: Unmodulated	0	None	Stylus Landing Check
B	72						
	*	Grey Field w/ Time Count	0:00 1:12 2:12/3:12	S1: Unmodulated S2: Unmodulated	1		Stylus Landing Adjustment
C	0						
	1						
	2	Uniform Motion on Grey Field		1020Hz 100%	2	None	Audio Level Adjust Mono Player Visual Search FWD/REV Check
D	6	Color Bars		S1: Unmodulated	3	None	Chroma and Video Adjustments General Picture Quality Check Stereo Indicator Check
E	10	100 IRE, White Field	100 IRE	S1: 480Hz 50% S2: 1020Hz 50%	4	Independent Not Encoded	Video Level Adjust Independent Audio Channel Test
F	13	Grey Field	Left Audio	S1: 1020Hz 50% S2: 1020Hz 50% In Phase	5	Stereo Encoded	Check and Adjust Stereo Separation Left Channel
G	15	Grey Field	Right Audio	S1: 1020Hz 50% S2: 1020Hz 50% Out of Phase	6	Stereo Encoded	Check and Adjust Stereo Separation Right Channel
H	19	120 IRE, 30% Window		S1: Unmodulated	7	None	Modulation Depth Adjust
I	23	5 Step Linearity w/ Defect		S1: Unmodulated	8	Mono Encoded	Defect Substitution Level Adjust
J	27 ⁰⁰⁰	Unmodulated (5MHz Carrier)		S1: Unmodulated	None		5.11MHz VCO Frequency Adjust
K	31	Demonstration		S1: Demonstration S2: 1020Hz 100%	10	Independent Not Encoded	General Picture and Sound Check
L	35	Grey Field	No Audio Carriers		11	None	Sound Beat Check
M	39	Grey Field	Audio 1	S1: 1020Hz 100% S2: Unmodulated	12	Independent-1 Not Encoded	Sound Beat Check
N	43	Grey Field	Audio 2	S1: Unmodulated S2: 1020Hz 100%	13	Not Encoded Independent-2	Sound Beat Check
O	47	Grey Field	Audio Decoder Reference	S1: 1020Hz 50% S2: Unmodulated	14	Stereo Encoded	Decoder Testing and Audio Output Measurement
P	49	Grey Field	Audio, -30db	S1: 1020 Hz 1.58% S2: Unmodulated	15	Stereo Encoded	Decoder Testing and Adjust
Q	51	Grey Field	Audio, -20db	S1: 1020Hz 5% S2: Unmodulated	16	Stereo Encoded	Decoder Testing
R	53	Grey Field	Audio, -10db	S1: 1020Hz 15.8% S2: Unmodulated	17	Stereo Encoded	Decoder Testing
S	56	Uniform Motion on Grey Field		S1: Unmodulated S2: Unmodulated	18	Stereo Encoded	Visual Search Check Background Noise Level Check
T	60	Vertical Lines w/ Time Count	0:00	S1: Unmodulated S2: Unmodulated	19	Independent	Armstretcher Check and/or Adjustment
U	62	Grey Field w/ Time Count	2:00/E	S1: Unmodulated S2: Unmodulated	63	None None	Daxl Signal Check For End of Recording
V	63	Grey Field w/ Time Count	3:00/5:00	S1: Unmodulated S2: Unmodulated	20	Independent Not Encoded	Arm Travel Limit Check

Note: Time count in Bands T, U and V is continuous (i.e., clock does not reset at the beginning of bands U and V). To access Band V, Rapid Access FWD must be used. Segment V ending time will depend on arm stop.

* See Service Data for use of pre-program segments of Bands A and B.

** Unless otherwise noted, Modulation/Deviation shown is for S1 only, and S2 is not present. (S1 = 716kHz carrier; S2 = 905kHz carrier).

*** Time Display will not increment when Daxl Band is not present (Segment J).

MECHANICAL OPERATION

Load Sequence

Pressing the on/off button (turning player on) applies power to the Function Motor. The function motor (running in the forward mode), drives the pulley and 1st reduction gear and the pinion and 2nd reduction gear which in turn drives the upper and lower power assist gears and caddy rollers. The upper power assist gear drives the power assist hub and rod assembly transferring power to the pawl drive gear that in turn drives the function gear. The function gear, as it rotates to the load position opens the caddy (sleeve) entry port door through mechanical linkage, operates the disc transfer rod and activates the mechanism load switch (S9). The digital display will display a flashing "L" indicating the player is in the "Load" mode (See Fig. 4).




Fig. 4—Mechanism Identification

Insertion of the loaded Caddy (sleeve) into the player first encounters the Pawl Actuating Crank lever which, through mechanical linkage, places the function gear actuating pawl in a non-actuating position. Encountered next the spine holddown pads, caddy lockout assemblies, and front receiver pads are raised and lowered respectively to allow caddy (sleeve) entry. The spindle receiver is then raised, the side receiver pads lowered and the caddy (sleeve) sense switch S4 activated (closed) by the caddy (sleeve).

When the caddy sense switch, S4, is activated (closed), power is applied to the function motor. The caddy (sleeve) rollers begin to rotate, they grasp the caddy (sleeve) pulling it into the player. The caddy (sleeve) then activates (closes) the caddy reverse switch, S8. As caddy (sleeve) insertion nears completion the rear receiver pads are lowered, the caddy (sleeve) lock defeat tabs enter the end of the caddy (sleeve) on either side unlocking the spine tabs which hold the spine and VideoDisc captive in the caddy (sleeve). At the same time the spine latch tabs, are pushed up and over the end of the spine and drop into their latching position holding the spine and VideoDisc captive in the player. The spine sense switch, S5, is also activated (closed) at this time and the side indicator switch, S6, is either activated (closed) or left "off" (open) depending upon which side of the disc is being played. The function motor stops for approximately one (1) second before it begins running in the reverse mode (See Figs. 5 & 6).

With the function motor running in the forward mode the caddy (sleeve) rollers will be driven in the reverse mode. This causes the caddy (sleeve), now empty, to be ejected automatically to a point just beyond the caddy (sleeve) entry door where it must then be manually removed.




Fig. 5—Mechanism Identification

As the caddy (sleeve), now empty, begins its ejection travel from the player—the caddy (sleeve) lock defeat tabs (spring loaded) pop up above the spine to the position necessary for performing their function during the "unload" process. The rear receiver pads rotate up to their normal position to support the disc and spine. The caddy (sleeve) reverse switch, S8, is deactivated (opens), however the function motor continues to run. When the caddy (sleeve) is released by the caddy rollers it must then be manually removed from the player. As the caddy (sleeve) is being manually removed from the player—the caddy sense switch, S4, is deactivated (opens), the side receiver pads (spring loaded) raise up to support the spine, the front receiver pads (spring loaded) raise and the spine holddown pads (also spring loaded) lower to support the disc and spine. The last item to be released is the Pawl Actuating Crank, which is used to prevent the function gear actuating pawl from being tripped during the time a caddy (sleeve) is in the player (See Figs. 5 & 6).

NOTE: The function motor, now controlled by the mechanism μ C, is still running in the forward mode.

Immediately upon release of the pawl activating crank the function gear actuating pawl is released, through mechanical linkage, and allowed to revert to its normal position. On the very next rotation of the pawl drive gear it strikes the function gear pawl placing the function gear




Fig. 6—Mechanism Identification

Continued on next page

MECHANICAL OPERATION (continued)

teeth, thus driving the function gear through its rotation. As the function gear is driven through its rotation several mechanical functions occur (via cams which are an integral part of the function gear) that operate mechanical linkage. The rear receiver pads are moved back slightly and the front receiver pads are moved forward slightly to allow the disc to be lowered onto the turntable. The caddy (sleeve) entry door is closed, the disc is lowered onto the turntable by the Disc Transfer Rod and the mechanism play switch, S7, is activated (closed). With the activation (closing) of the mechanism play switch the turntable powers up and the arm assembly is moved into position over the disc, the stylus drops making contact with the disc producing picture and sound on the monitor television.

NOTE: A time lapse of approximately 10 seconds is required from turntable power up until picture and sound appear on the monitor TV.

Stylus Clean

The stylus is cleaned during the time the arm assembly is moved forward from its "home" position to its "play" position over the disc. The stylus cleaner pad is spring loaded and moves forward on an angle controlled by the arm assembly. About half-way through the forward movement of the stylus cleaner pad assembly the arm assembly hesitates (stops momentarily), the stylus is dropped and then the arm assembly and stylus cleaner pad continue their forward movement dragging the stylus across the cleaner pad in a parallel path cleaning the stylus. Almost immediately the stylus lifter circuit is activated lifting the stylus off the cleaner pad. When the stylus cleaner pad reaches the end of its travel the arm assembly continues its forward movement and positions itself over the disc at a predetermined starting point controlled electronically by activation of Landing Switch S10, contacts 1 & 2. The stylus is then dropped onto the disc to begin its function during the "Play" process (See Fig. 7).




Fig. 7—Stylus Clean

Unload

At "end-of-play" the digital display will display a flashing "E" for a period of approximately four (4) seconds, then display a non-flashing "E" during the time the arm assembly is being returned to its "Home" position. When the arm assembly reaches its home (outermost) position, Landing Switch, S10, is deactivated (open) and Arm Home switch, S11, is activated (terms. 1 & 3 closed). The stylus cleaner pad is also forced to its outermost position by the arm assembly and the turntable electronically seeks its locked position.

When the arm assembly reaches its Home position Arm Home switch, S11 opens permitting the function motor to be activated in the reverse mode. With the function motor running in the reverse mode the function gear is rotated through its cycle opening the caddy (sleeve) entry door, through mechanical linkage, and the VideoDisc is raised to the "Unload" position by the Disc Transfer Rod.

NOTE: There is a 5 minute time-out period in the "unload" mode. If the disc and spine is not removed during this period the disc is returned to the turntable and the player places itself in the "Pause" mode.

Insert empty caddy (sleeve) through the caddy (sleeve) entry port door in the same manner used when the player was loaded. The same series of events will occur as occurred during the "Load" sequence with the following exceptions. The caddy (sleeve) makes contact with the caddy lock defeat tabs (these are the tabs used to release the spine and VideoDisc from the caddy during the "load" process and sprang up when the caddy was removed) forcing them up over the caddy (sleeve) which in turn forces the spine latch tabs to release the spine. The spine and VideoDisc are forced into the empty caddy (sleeve) by the spine push back springs locking it securely. The caddy (sleeve), with the spine and disc locked securely inside, can now be safely ejected by the caddy rollers. When the caddy (sleeve) is removed past the caddy sense switch S4, the switch is deactivated removing power from the function motor. The player automatically reverts to the "Load" mode. At this time the loaded caddy may be turned over and re-loaded in the player to play the other side of the VideoDisc. DO NOT leave the player in the "Load" mode for any extended period of time. Dust or other contaminants could enter the mechanism through the open caddy entry port door and cause damage to the unit (See Fig. 8).

MECHANISM OFF ACTUATOR




Fig. 8—Unload and Off

Off Position (Disc and spine removed)

Pushing the "OFF" button (to turn player off) makes the player think it has been loaded with a disc. The function motor runs in the forward mode operating the function gear which begins rotating as if to drop a disc on the turntable. However with no spine in the player the mechanism "OFF" actuator comes into play. At about half-rotation of the function gear, a cam (an integral part of the function gear) forces the mechanism "OFF" actuator up against mechanism AC switch, S2, turning it off (open) removing AC power from the player. The same cam also operates

ELECTRONIC SYSTEMS DESCRIPTION

mechanical linkage which closes the caddy entry port door and holds the Lockouts and Pawl Actuating Crank rigid preventing insertion of a loaded caddy into the player in the "OFF" position (See Fig. 8).

Fig. 46 - is a combined electrical system block diagram of RCA SJT 100/200/300 VideoDisc players. The SJT 100 being the basic VideoDisc player with monaural audio, the SJT 200 being a stepped-up version of the SJT 100 featuring video output and stereo audio output, and the SJT 300 being a stepped-up version of the SJT 200 featuring Remote Control and Hi-Speed scan. Most electronic circuits in the VideoDisc player can be separated into two basic functional categories; PLAYER CONTROL and SIGNAL PROCESSING. One large Master Circuit Board contains the majority of the electronic circuits in the VideoDisc player.

A micro computer (μ C) integrated circuit is the heart of the player control function. The micro-computer receives input commands from the user-operated function switches and, in turn, controls the operation of the player. The player control μ C also decodes the **Digital Auxiliary Information** (DAXI) on the VideoDisc to develop the elapsed playtime readout and to control the forward movement of the pick-up arm assembly during the "Play" mode. The signal processing circuits are equipped with several integrated circuits and discrete devices, the majority of which are mounted on the master circuit board assembly with the remainder being on the pick-up arm assembly. The signal processing circuits detect the video and audio information on the VideoDisc, demodulates it and processes it through a comb-filter circuit, and then modulates it onto either a channel 3 or channel 4 television RF carrier. This modulated television RF carrier signal is then connected through coaxial cable to any NTSC television receiver.

Functional Operation

Operation of the VideoDisc player is totally controlled by the player control micro-computer. When the user selects an operating mode—**Rapid Access Forward or Reverse, Visual Search Forward or Reverse, Pause/Play or Reject**—input commands related to that mode are fed to the microcomputer. The microcomputer decodes these input commands and, in turn, uses the decoded information to "direct" other player control electronics to establish the electrical conditions required to perform the selected mode of operation. The state of all signal processing circuits is controlled by the Not Squelch (SQ) output of the player control microcomputer. When the Not Squelch line goes to a logic "Lo" state, all of the signal-processing electronic circuits are disabled (squelched).

The player control microcomputer has direct control over the pickup arm assembly and the mechanism control microprocessor. This involves:—operation of the Function motor (to "Load" and "Unload" the player); — the turntable motor; — the arm drive (stepper) motor operation, moving the arm forward (Toward center of disc) during normal play — the stylus lifter operation, raising and lowering the stylus as the various functions are initiated; — and the stylus kicker circuits, enabling the system to provide the **VISUAL SEARCH** feature. The player control microcomputer also controls the direction of the arm drive (stepper) motor. In the **RAPID ACCESS REVERSE**, and **VISUAL SEARCH REVERSE** operating modes, the microcomputer instructs the arm drive (stepper) motor to operate in the reverse mode. The player control microcomputer also generates the elapsed play time dis-

play. The time display information is developed from the Digital Auxiliary Information (DAXI) signal. This signal is pre-recorded on the VideoDisc on line 17 of each vertical field. The DAXI signal includes a field identification number that is decoded by the player control microcomputer. This decoded information is used by the microcomputer to develop the elapsed time display. The DAXI code is not present in the **RAPID ACCESS FORWARD** or **REVERSE** operating modes because the stylus is lifted from the disc. Therefore, during these two modes of operation the time display must be alternately maintained so that the approximate elapsed time of the program material can be tracked while the stylus is lifted and the arm is moved in either direction across the disc. This is accomplished by the player control microcomputer counting the steps taken (either forward or reverse) by the arm drive (stepper) motor, then computing the approximate elapsed time by tracking the position of the arm relative to the disc radius.

The signal processing electronics on the pickup arm assembly detect information recorded on the VideoDisc. The arm also contains components for providing the features of **VISUAL SEARCH FORWARD** and **REVERSE** as well as locked groove protection. They are: the "stylus kicker" coils which will cause the stylus to skip two grooves of the VideoDisc; the "armstretcher" transducer which corrects for the timebase variations in the recovered chrominance and luminance signals.

NOTE: The arm assembly of VideoDisc player Model SJT 300 also contains an **in arm** stylus sweeper which is activated when the player goes into carrier distress and remains there for a period of 3 seconds. It is also activated each time the player is placed in the "Pause" mode.

The primary function of the pickup arm signal processing electronics is to detect the information recorded on the VideoDisc. This is accomplished by modulating a 910 MHz VHF resonator circuit with the capacitance changes on the VideoDisc surface. The variations in capacitance on the VideoDisc surface causes the 910 MHz resonator center frequency to be modulated. This, in turn, amplitude modulates a fixed 915 MHz oscillator signal. The signal is then peak detected, with the resultant signal representing the capacitance variations on the VideoDisc. The signal is then preamplified and AFT controlled before being applied to the remaining signal processing electronics. The Arm Output (AO) signal contains the video and audio FM-modulated carrier information and all of the information (DAXI) necessary for player control.

The AO signal is applied to the Main Circuit Board assembly where it is distributed to the player control electronics, the video signal processing electronics, and the audio processing electronics.

In the signal processing electronics of the monaural VideoDisc player (SJT 100) the AO signal is applied to two (2) FM demodulator ICs one for video processing and one (1) for audio processing. In the signal processing electronics of the stereo VideoDisc player (SJT 200/300) the AO signal is applied to three (3) FM demodulator ICs. One (1) for video processing and two (2) for audio processing.

In the case of a Monaural VideoDisc a single audio track is imprinted on the disc at 716 kHz. In the case of a stereo or bilingual VideoDisc two (2) audio tracks are imprinted on the disc. One at 716 kHz, the other at 905 kHz.

Before the AO signal is applied to the Video Demodulator IC, it is passed through a Non Linear Aperture Correction

Continued on next page

ELECTRONIC SYSTEMS DESCRIPTION (continued)

(NLAC) circuit. The NLAC circuit removes the 716 kHz audio modulation from the video information. It does this by phase inverting the audio modulation, and then adding it back to the original signal. This cancels out the 716 kHz audio modulation in the carrier information. The video FM carrier, with the 716 kHz audio modulation removed is then applied to the Video demodulator IC and a Pulse Interference Corrector (PIC) circuit.

The purpose of the Pulse Interference corrector (PIC) circuit is to prevent radar and other strong RF pulses in the 900 MHz range from interfering with the operation of the VideoDisc Player. The PIC circuit detects the presence of such pulses and instructs the defect corrector in the Comb Filter and Defect Corrector integrated circuit to substitute the previous line of video information.

The Video Demodulator IC, which demodulates the video carrier, also contains a defect detector circuit used to activate the defect corrector in the comb filter IC. Thus allowing a portion of the previous horizontal line to be inserted when a defect caused by loss of carrier occurs. The output of the video demodulator, being composite video with "buried" subcarrier chroma, is then applied to a comb-filter circuit. The comb-filter dynamically separates chrominance and luminance information from the composite video information. The output of the comb filter is "combed" chrominance and "combed" luminance. The combed chrominance output signal contains low frequency luminance information and the DAXI signal which is transmitted with each vertical field. After bandpassing the 1 to 2 MHz chroma signal, the two remaining signals (low frequency luminance and DAXI) are separated by low pass filters. The low frequency luminance information is recombined with the "combed" luminance information to provide the luminance output. Vertical Detail Output (VDO) containing the DAXI signal is supplied via the DAXI buffer IC to the player control microcomputer.

The luminance and chrominance information is coupled from the comb-filter circuit to the video converter circuit. The video converter up-converts the 1.53 MHz chrominance information to 3.58 MHz. The 3.58 MHz chroma and the luminance information are then combined. The resultant composite video signal is then supplied to the RF modulator where the demodulated audio signal is added and a RF signal on channel 3 or channel 4 is developed for output to a standard NTSC television receiver.

Also developed in the video converter stage is the drive signal for the "Armstretcher" time base corrector circuit. The correction signal is developed by comparing the up converted 3.58 MHz chroma information with a crystal controlled 3.58 MHz reference oscillator. Any phase or frequency difference between the two signals develops an error signal which is applied to the arm-stretcher circuit. The armstretcher circuit operates a solenoid (located on the pick up arm assembly) moving the stylus (laterally with respect to the disc) to maintain a constant disc to stylus velocity. The armstretcher circuit output is also coupled to the converter oscillator (5.11 MHz VCXO) in order to maintain phase lock between the up converted 3.58 MHz color signal and the crystal controlled 3.58 MHz reference oscillator.

A Video Noise Coring circuit is used in conjunction with the video converter circuit to eliminate high frequency signals below 5 IRE peak-to-peak from the composite video output signal. The "combed" luminance signal is

capacitively coupled to a noise coring amplifier stage where it is inverted. The inverted signal is then direct coupled to a non-inverting noise coring buffer stage. The non-inverted signal is coupled back to the input circuit of the noise coring amplifier stage through a coring circuit consisting of a coupling capacitor and two (2) coring diodes. This represents a negative feedback of all signals above 5 IRE peak-to-peak which is 180 degrees out-of-phase with the incoming signal. Therefore all signals above 5 IRE will be cancelled at the input of the noise coring amplifier stage. Hence, the signal at the output of the noise coring buffer stage will contain only signals below 5 IRE peak-to-peak. This signal is then added, 180 degrees out-of-phase, to the composite video signal from the video converter IC. The result being elimination of high frequency signals below 5 IRE peak-to-peak from the composite video output signal, thus reducing high frequency noise in the video information.

Audio Signal Processing

As previously stated, in the case of a monaural VideoDisc a single audio track is imprinted on the disc at 716 kHz. The AO signal is applied to a Band pass filter which passes only the 716 kHz audio information. This information then is applied to the 716kHz Audio FM Demodulator IC. After demodulation the signal is coupled to a Sample and Hold CMOS switching IC. The audio signal then is capacitively coupled to the RF Modulator circuit.

In the case of a Stereo or Bilingual VideoDisc two (2) separate audio tracks are imprinted on the disc—one at 716 kHz the other at 905 kHz. The AO signal is applied to two (2) Band Pass Filters one of which passes only the 716 kHz audio signal and the other passes only the 905 kHz audio signal. The audio signals are then applied to two (2) audio demodulator IC's. The 716 kHz signal is processed by the (L+R) audio demodulator IC and the 905 kHz is processed by the (L-R) audio demodulator IC.

The signals are then routed through a TRACK/HOLD and MUTE CMOS Switching IC. The (L+R) signal is applied to a non-inverting OP Amp and then to the base of the Right and Left channel audio buffer stages. The (L-R) is applied to a non-inverting OP Amp and then to the base of the Left channel audio buffer stage. It is also applied to an inverting OP Amp, which provides the necessary inversion of the (L-R) signal, the output of which is applied to the base of the right channel audio buffer stage.

Separation takes place in the base circuit of the left and right channel audio buffer stages. With both (L-R) and (L+R) signals present at the base of the left channel audio buffer the right channel information is cancelled leaving only the left channel information at its output. Likewise with both [-(L-R)] and (L+R) signals present at the base of the right channel audio buffer the left channel information is cancelled leaving only the right channel information at its output.

The output of the left and right audio buffers (now separated audio) is applied to three (3) circuits. First is the transconductance audio output amplifier IC; second the right and left audio signals are applied to the noise reduction decoder circuit which generates a gain control signal and couples it back to the transconductance audio output amplifier; third, the right and left audio signals are summed together and coupled via the CMOS switching IC to the RF modulator circuit. After final amplification by

Continued on next page

ELECTRONIC SYSTEMS DESCRIPTION (continued)

audio output IC the audio signals are then de-emphasized and applied to their respective audio output jacks.

The ON or OFF state of the Track/Hold and Mute electronic CMOS switching IC is electronically determined by the DAXI code imprinted on the VideoDisc being played. In the case of a monaural disc, the portions of the CMOS switch IC Controlled by pins 5, 6 & 13 (pins 5, 6 & 13 go to high state) will be activated allowing the 716 kHz (or right channel audio) to be passed for processing. In the case of a stereo disc, the portions of the CMOS switch IC controlled by pins 5, 6 & 12 (pins 5, 6 & 12 go to high state) will be activated allowing both the 716 kHz (right channel audio) and 905 kHz (left channel audio) to be passed for processing. In the case of a bilingual VideoDisc, the state of the CMOS switches depends on which audio channel you choose to operate. If you choose to operate primary channel "A", CMOS switching IC pins 5, 6 and 13 will be "high" allowing only channel "A" (716kHz) information to be passed for processing. If you choose secondary channel "B", CMOS switching IC pins 12 and 13 will be "high" allowing only channel "B" (905 kHz) information to be passed for processing.

Muting is accomplished by placing pins 5 and 12, of the CMOS switching IC, in a "low" state thereby opening their respective switch sections.

Decoder Operation

The original Stereo audio signal stamped onto the VideoDisc is compacted from a dynamic range of (+12db to -40db) to (+6db to -20db) for recording on the disc itself. To reproduce the original stereo audio signal a decoder system has been incorporated in the "Stereo" VideoDisc Player audio signal processing circuitry. The audio signal from each channel is coupled via a 100 Hz

high pass filter into a pair of Op Amps. One is an inverting amp the other noninverting. All four of these Op Amps, tied together at their outputs, perform like a full wave rectifier. Another Op Amp, whose output is controlled by a fixed bias, sets the output of the rectifier stages. This permits a maximum signal expansion of (-20db) changed to (-40db) point level. The output of the rectifier Op Amps is then coupled to a decoder Op Amp (works like a filter) whose output is applied to another decoder Op Amp (a DC amp) creating a variable DC voltage at its output. This variable DC voltage is then processed by a time constant network which performs the actual decoding function. The output of the time constant network is then applied to an additional Op Amp. The output of this Op Amp (also a variable DC voltage) is used to control the current flow through a Current source transistor. The output of the current source transistor then is used to control the gain of the transconductance amplifier stages for both the Left and Right Channel audio output.

NOTE: The decoder circuit is operational only when playing a Stereo encoded (compacted) VideoDisc. When a monaural or bilingual VideoDisc is being played a fixed bias is applied to the Op Amp immediately preceding the decoder time constant network. This in turn places a constant bias on the Transconductance amplifier stages in the Audio Output Integrated Circuit.


Video Output is provided on Stereo VideoDisc players (SJT 200/300). The composite video signal is tapped off, just prior to being applied to the RF Modulator stage, and applied to a Video buffer stage. The output of the Video Buffer stage is connected to a video output jack on the rear of the player. This provides a 1V p-p video output signal when terminated with a 75 ohm load.

TURNTABLE HEIGHT ADJUST

To check turntable height—With disc in player in "Play" mode remove AC cord from power source. Remove stylus cartridge and store in safe place. Insert turntable height gauge (see replacement parts list for Stock No.). Hold height gauge in Arm Assembly firmly. Be sure height gauge plunger is free to indicate properly (see illustration).

- If gauge plunger remains on lowest step—raise turntable height by adjusting height adjust screw (Item —, Fig. 42) clockwise.
- If gauge plunger moves to highest step—lower turntable height by adjusting height adjust screw counterclockwise.
- Proper turntable height—when gauge plunger passes over lowest step on gauge and does **not** pass over highest step.

CAUTION: Use old disc or reserve one side of test disc for this adjustment. DO NOT use a good disc for this procedure.



Turntable Height Gauge

NOTE: Turntable height adjust screw is an Allen head screw accessible from the bottom with a (1/16") Allen wrench. Some instruments may use a locking screw (same size). First try turning screw clockwise, if screw will not turn with slight pressure the instrument uses a locking screw which must be removed to accomplish turntable height adjust. Replace locking screw when adjustment is complete.

INSTRUMENT DISASSEMBLY

Cabinet Top Removal

- Place instrument in "off" mode—remove power plug from 120V AC power source.
- Remove two (2) posi-drive (+ head) screws Fig. 2.
- Grasp cabinet top at bottom edge on either side (towards the rear). Pull up and to the rear freeing cabinet top front lip from under the front panel and remove cabinet top.
- To reassemble—reverse procedure.

Front Panel Removal

- With cabinet top removed and player in "Play" mode—remove AC cord from power source. Use needle nose pliers and carefully remove door push rod spring from front receiver pad (left and right sides) Fig. 9.
- Grasp front panel along top rear edge—lift rear edge slightly and pull front panel away from player.
- Remove flex cable plastic cover, disconnect flex cable connector and remove front panel.
- To reassemble—reverse procedure.

NOTE: When removing front panel it is necessary that the arm assembly be placed in its forward most position. See stylus cartridge removal for procedure.




Fig. 9—Door Push Rod Spring




Fig. 10—Bottom Cover

Bottom Cover Removal

- Remove stylus cartridge and store in safe place. Place instrument, bottom up, on workbench with soft surface. If cabinet top has been removed also remove receiver spindle assembly (Fig. 14).
- Remove adjusting nut (1/2 inch Hex Head) and reinforcing plate (1 1/4" washer) from center of bottom cover.
- Remove five (5) posi-drive (+ head) screws Fig. 10.
- To replace—reverse procedure.

NOTE: When replacing Bottom Cover—just start adjusting nut and screw. Properly seat Bottom Cover then: (a.) tighten screws (b.)tighten adjusting nut.

Master Circuit Board Removal/Service Position

- Remove cabinet top and receiver spindle assembly, and stylus cartridge place instrument bottom up on workbench with soft surface and remove bottom cover.
- Remove ten (10) posi-drive (+ head) screws Fig. 11.
- Remove main circuit board by lifting front edge up to approximately a 10° to 15° angle, so as to clear all obstacles, then move board forward towards front of instrument until antenna connectors clear rear edge of base plate.
- After circuit board is clear of baseplate rotate board horizontally 90° and lay beside instrument.
- Turn bottom plate over and fasten in position on baseplate with center adjusting nut and reinforcing plate (1 1/4" washer).

NOTE: Bottom plate must be installed in prescribed manner to operate instrument in service position.

- Place instrument and circuit board in upright position (Fig. 12), reinstall receiver spindle assembly and reconnect front panel flex cable to flex cable connector. Instrument is now in operational service position.
- To reassemble—reverse procedure.




Fig. 11—Master Circuit Board

INSTRUMENT DISASSEMBLY (continued)




Fig. 12—Service Position

Arm Drive Assembly Disassembly

1. With cabinet top and front panel removed—remove one (1) posi-drive (+ head) screw Fig. 13.
2. Unsolder and remove Brn. and Wht/Brn wires from radius sense control.
3. Remove stepper motor from arm drive assembly by removing two (2) small posi-drive (+ head) screws and lay stepper motor to the side out of the way.
4. Move arm drive assembly toward center of player and lift up to remove from player.
5. To replace any gear—first remove wire nut from 3rd reduction gear mounting stud and remove 3rd reduction gear. The 2nd and 1st reduction gears are now accessible.
6. To reassemble—reverse procedure. Be certain ESD ground spring is dressed to the outside of stepper motor mounting screw.

NOTE: After replacing arm drive assembly—apply power to player. "Load" player with a VideoDisc and *rapid access* arm assembly to its *innermost* position. Reject player and unload VideoDisc. If a clicking noise is heard during this procedure—disregard—the radius sense control gear is resetting itself. Be certain during this procedure that the arm assembly does indeed reach its innermost and arm home positions.




Fig. 13—Arm Drive Assembly

Stylus Cartridge Removal

1. With cabinet top removed—remove AC plug from power source.
2. Using thumb—rotate 2nd reduction gear (Fig. 14) in counter clockwise direction moving the arm assembly to a point where the stylus cartridge access cover (lid) is accessible.
3. Using a small blade screwdriver—unlatch stylus cartridge access cover (lid) latch spring and open access cover (lid).
4. Using thumb and forefinger—grasp stylus cartridge and push it slightly to the right against the arm-stretcher coil assembly. With a rocking motion lift left end of cartridge slightly, then lift cartridge straight up and out of arm assembly.
5. To replace—reverse procedure.




Fig. 14—Stylus Cartridge and Receiver Spindle

Receiver Spindle Assembly Removal

1. With cabinet top removed—rotate receiver spindle assembly to a vertical position (Fig. 14).

Continued on next page

INSTRUMENT DISASSEMBLY (continued)

2. Move receiver spindle assembly to the left until the right side just clears the right rail assembly.
3. Lift up on right side of receiver spindle assembly until it clears the right rail assembly.
4. Move receiver spindle assembly to the right until it clears the left rail assembly and remove the receiver spindle assembly from the player.
5. To replace—reverse procedure.

Stepper Motor Removal

1. With instrument in service position—remove stepper motor plug, P2, from main circuit board.
2. Cut four (4) wire ties and pull stepper motor cable and plug assembly up through baseplate.
3. Remove two (2) small posi-drive (+ head) screws used to mount stepper motor and remove stepper motor (Fig. 13).
4. To replace—reverse procedure. Replace wire ties and observe original lead dress.

Function Motor Removal

1. With cabinet top removed—disconnect Blu and Wht/Blu wires from function motor (observe polarity).
2. Remove two (2) posi-drive (+ head) screws and remove gear cover Fig. 16.
3. Remove square drive belt Fig. 16.
4. Remove two (2) small posi-drive (+ head) screws and remove function motor.
5. To replace—reverse procedure.

NOTE: When replacing Function Motor observe polarity of wiring. Solid blue wire connects to stake beside small plastic stud.

Guide Rail Assembly Removal

1. Place player in "Load" mode and remove AC plug from AC power source. With cabinet top and front panel removed—remove guide rail assembly front support bracket ESD ground spring Fig. 15, and ground clips from guide rail bracket and pivot support brackets.
2. Remove one (1) small posi-drive (+ head) screw from S2 AC switch shield and remove shield (items 45 & 44, Fig. 47).
3. Remove AC switch, S2, from right rail assembly.
4. Remove AC fuse shield from PW 600 circuit board and mounting bracket assembly.

NOTE: Removal of PW600 circuit board is not necessary for guide rail assembly removal. However it is recommended for ease and convenience.

5. Unsolder and remove AC input cord from PW600 and remove PW 600 circuit board from bracket assembly. One plastic clip located at the front top edge of mounting bracket holds the circuit board captive. Carefully lift up on this plastic clip and separate circuit board and mounting bracket, then lift straight up on circuit board until it is free of the baseplate. Lay circuit board to right side.

6. Remove PW 600 plastic mounting plate. Use 1/4" blade screwdriver through access holes along bottom edge of plate to spring plastic clips holding plate captive to baseplate and lift mounting plate straight up and free of baseplate. Remove switches S7 and S9 from plate assembly.

CAUTION: Switches S7 and S9 are mounted on the plate assembly by molded plastic clips and studs, use special care when removing and replacing switches to avoid breaking them.

7. Grasp mechanism AC switch (S2) off actuator (item 47, Fig. 47) between thumb and forefinger and pull actuator back and free of right rail assembly and function gear (some pressure will be required to perform this step).

8. Using thumb rotate mechanism 2nd reduction and pinion gear in a clockwise direction until the function gear on right rail assembly is engaged. Continue rotating gears until the disc transfer rod coupler (item 38, Fig. 47), mounted on function gear, reaches its top most position. This is the mechanism (player) "off" position.
9. Remove disc transfer rod from coupler and remove coupler from function gear.
10. Remove switches S4 and S8 from left rail assembly and place them out of the way.

CAUTION: Switches S4 and S8 are mounted on the left rail assembly by molded plastic clips and studs, use special care when removing and replacing switches to avoid breaking them.

11. Unsolder function motor leads—observe polarity for replacing.
12. Remove three (3) posi-drive (+ head) screws (Fig. 15).
13. Lift guide rail assembly to about a 45° angle. Move guide rail assembly toward rear of player unseating one side at a time, and lift straight up to remove from mounting brackets molded into player baseplate. (see Note) Guide rail assembly is now free to be removed from player.

NOTE: For ease in removal use slight pressure to unseat each side individually, Guide Rail assembly snaps into base plate mountings.

14. To reassemble—reverse procedure.




Fig. 15—Guide Rail Assembly

Guide Rail Assembly Disassembly

1. With guide rail assembly removed from player—remove retaining rings from function gear and receiver actuator (Fig. 17).
2. Release front receiver activating rod (Fig. 17) held captive by plastic tab on right rail assembly.
3. Pull both the function gear and receiver actuator away from rail assembly slightly. Push function gear

Continued on next page

INSTRUMENT DISASSEMBLY (continued)




Fig. 16—Left Guide Rail Assembly




Fig. 17—Right Guide Rail Assembly

pawl out of the way and position function gear to clear receiver actuator. Remove function gear and then the receiver actuator.

- Remove side receivers (one each side)—release spring and rotate receiver to 45° angle. Slide receiver toward front of rail assembly and remove from rear mounting bracket by angling rear of receiver away from rail, slide receiver toward rear of rail assembly to complete removal.
- Remove receiver actuator rod (Fig. 17) from right rail assembly and side receiver wire cam (Fig. 16) from left rail.
- Remove retaining ring holding pawl drive gear (Fig. 17) captive—remove pawl drive gear.
- Remove retaining ring holding the power assist gear (Fig. 17) captive. Remove power assist gear.
- Remove lock out springs (Figs. 16 & 17) right and left sides. Remove caddy lockouts (Figs. 16 & 17).
- To separate the Left and Right rail assemblies the cabinet support bracket (Fig. 18) and the pivot support bracket (Fig. 18) must be removed.
- Use small blade screwdriver (approximately $\frac{1}{8}$ "")—slip between plastic overlap of rail assembly and top of cabinet support bracket and pry up to remove bracket. Repeat same procedure at rear of pivot support bracket.

CAUTION: Some pressure must be exerted during this procedure, however care must be taken to avoid breaking plastic rail.

NOTE: Brackets simply snap into place during replacement.

- Remove spacer (Item 52, Fig. 47) from right rail assembly (holds spine hold down assembly in place on right rail assembly). Remove spine hold down assembly (Item 53, Fig. 47).
- Remove power assist hub assembly (Item 32, Fig. 47) and front receiver pad assembly (Item 51, Fig. 47).
- To reassemble—reverse procedure.




Fig. 18—Guide Rail Assembly

INSTRUMENT DISASSEMBLY (continued)

Rear Receiver Pad Assembly Removal

- With guide rail assembly and turntable removed—release tension on rear receiver pad assembly torsion spring (Fig. 19) and remove wires to switch S8 from wire guide stud. Move switch and wire out of the way.
- Lift rear receiver pad assembly (Fig. 19) straight up and remove from baseplate.
- To replace—reverse procedure.

NOTE: Before replacing rear receiver pad assembly in position apply one (1) full turn of tension to torsion spring.

Caddy Defeat and Spine Latch Assembly Removal

- With guide rail assembly removed—release caddy defeat springs (Fig. 19) from baseplate studs.
- Remove spacer clip (Fig. 19) from caddy defeat and spine latch assembly.
- Slide caddy defeat and spine latch assembly (Fig. 19) to right—raise left side of assembly to clear mounting stud and slide assembly to left to remove.
- To replace—reverse procedure.

Disc Transfer Rod Removal

- With Guide Rail, Rear Receiver Pad and Caddy Defeat/Spine Latch assemblies removed—release Transfer Rod spring (Fig. 19) from baseplate stud.
- Rotate Transfer Rod (Fig. 19) upward to clear center portion of baseplate.
- Move Transfer Rod to the left to clear far right mounting stud. Rotate rod toward rear of player to clear next mounting stud and continue moving rod to the left.
- After the first large mounting stud has been cleared by transfer rod, guide left portion of rod up and toward rear of player. Drop right portion of rod into trough molded into baseplate.
- Using an upward arcing motion continue moving rod




Fig. 19—Miscellaneous Disassembly

until it can easily be lifted up and out of the center baseplate mounting studs.

- To replace—reverse procedure.

NOTE: No force is required to remove or replace the disc Transfer Rod.

Turntable Removal

- With cabinet top, receiver spindle assembly and guide rail bracket removed—use thumb to rotate mechanism drive 2nd reduction gear (Fig. 16) in direction necessary to place mechanism in "PLAY" mode while holding AC switch (S2) actuator (Item 47, Fig. 47) back out of the way.
- Rotate turntable to center solid portion of turntable over transfer rod (two holes in turn-table at 45° angle with respect to rear edge of player).
- Lift up on turntable and angle front edge of turntable to clear front receiver pad and remove turntable from player on an angle.
- To replace—reverse procedure.

NOTE: When replacing turntable—be certain to check magnet and turntable well for debris.

CAUTION: There is a thrust plate (Item 102, Fig. 48) used in the turntable bearing. Be sure that it is in place before replacing turntable. Do not turn player upside down during servicing without turntable in place, it could result in possible loss of the thrust plate.




Fig. 20—Turntable and Arm Assembly

Arm Assembly Removal

- With cabinet top, cabinet front and receiver spindle removed—remove cabinet support bracket ESD ground spring from left front corner.
- Remove ground clips from guide rail bracket and pivot support bracket. Remove stylus cartridge from arm assembly and store in safe place.
- Remove Arm Drive Assembly from baseplate and move to the side out of the way.
- Remove three (3) posi-drive (+ head) screws holding

Continued on next page

INSTRUMENT DISASSEMBLY (continued)

- guide rail assembly and lift assembly to 45° angle. (Fig. 20).
5. Unsolder shielded AO cable from PW 400, arm preamp circuit board. Remove cable strap and P 101 from arm interconnect circuit board.
 6. Lift Arm Carriage Shaft (Fig. 20) from its rear baseplate mounting and pull it loose from its front baseplate mounting.
 7. Remove Arm assembly from player.
 8. To replace—reverse procedure.

PW 200 Resonator Removal

1. Remove stylus cartridge and store in safe place.
2. Remove two (2) posi-drive (+ head) screws holding resonator captive and remove stylus cover latch spring (Fig. 21).
3. Unsolder three (3) wires connected to feed-thru studs on resonator.
4. Lift resonator up to remove from Arm Assembly.
5. To replace—reverse procedure.

Lifter Actuator Assembly Removal

1. Remove cartridge cover and stylus cartridge. Place stylus cartridge in safe place.
2. Remove two (2) lifter pivot retaining clips—one (1) each side of arm assembly (Fig. 21).
3. Remove Lifter Actuator assembly.




Fig. 21—Arm Assembly SJT 100/200

FIELD SERVICE ALIGNMENT PROCEDURES**Test Equipment Required:****Digital Voltmeter****Specifications**Range: .1V DC to 30V DC
Accuracy: ±1%**Oscilloscope**Triggered
Response: DC – 20 MHz.
Sensitivity: 5mV/cm
Maximum Sweep Rate .1μS/cm**Frequency Counter**Range: 50 Hz to 100 MHz.
Sensitivity: 25mV to 5V**VideoDisc**

Stereo Alignment Disc: See Replacement Parts List for Stock No.

Color TV Receiver

Standard NTSC

Marker Generator

Range: Crystal Calibrated from 19 to 262 MHz.

Alignment Tools2.5mm non-metallic female
Hex Head adjustment tool
(see replacement parts list for Stock No.)
.056" square end tool GC9440 or equivalent
.100" hex end tool GC8606 or equivalent
insulated blade tool GC8722 or equivalent**ELECTRICAL ADJUSTMENTS**

NOTE: Use only the Stereo Alignment (TEST) Disc (see replacement parts list for stock no.) to perform the following adjustments.

5V Reference Adjust R2020

1. Apply power to player and place in "Load" mode.
2. Connect DC Voltmeter to TP 2003 (Fig. 26).
3. Adjust R2020 for 5.0V DC ± .05V DC (Fig. 27).

3.58 MHz Reference Oscillator Adjust

1. Connect frequency counter via X10 probe (see note) to TP 3406 (Fig. 26).
2. With player in "Load" mode adjust C5902 for 3.579545 ± 10 Hz (Fig. 27).

NOTE: Typical capacity of X10 probe and counter is approximately 20-25pf. A X1 probe (typical capacity of 100 pf) may be used with a 33pf capacitor placed in series with probe. This will place a load on the VCO of approximately 25pf.

NLAC (DC Balance) Adjust (R3131)

1. Place player in "Pause" mode.
2. Connect DC Voltmeter to TP 3101 (Fig. 26).
3. Adjust R3131 to produce a 10.5 ± 0.5 V.D.C. reading (Fig. 27).

Video Demodulator VCO Adjust (C3215)

1. Apply power to player.
2. Disconnect interconnect plug P4 (A0).
3. Short the two pins of J4 together.
4. Connect frequency counter via X10 probe (see note) to TP 3102 (Fig. 26).
5. Adjust C3215 for 5.25 MHz ± 50 KHz (Fig. 27).
6. Remove short from the two pins of J4 and reconnect P4.

NOTE: Typical capacity of X10 probe and counter is approximately 20-25pf. A X1 probe (typical capacity of approximately 100pf) may be used with a 33pf capacitor placed in series with probe. This will place a load on the VCO of approximately 25pf.

Video Level Adjust (R3202)

1. Place player in "Play" mode.
2. Use stereo alignment disc 100 IRE white field signal (Segment E).
3. Connect oscilloscope to TP 3410 (Fig. 26).
4. Adjust R3202 (video level adjust) to produce 2.8Vp-p response at TP 3410 (Fig. 27).

Luminance Channel Null Adjust R3328

1. Place player in "Play" mode.
2. Use stereo alignment disc color bar signal (Segment D).
3. Connect oscilloscope to TP 3302 (Fig. 26).
4. Adjust R3328 for minimum (null) chroma information. See Figs. 22 & 27.




Fig. 22—Luminance Null

ELECTRICAL ADJUSTMENTS (continued)

Chroma Channel Null Adjust R3329

1. Place player in "Play" mode.
2. Use stereo alignment disc color bar signal (Segment D).
3. Connect oscilloscope to TP 3303 (Fig. 26).
4. Adjust R3329 for minimum p-p signal see Figs. 23 & 27.

NOTE: Repeat Video Level Adjustment after completion of Luminance Channel Null and Chroma Channel Null adjustments.




Fig. 23—Chroma Null

Chroma Level Adjust R3312

1. Place player in "Play" mode.
2. Use stereo alignment disc color bar signal (Segment D).
3. Connect oscilloscope to TP 3410 (Fig. 26).
4. Adjust R3312 so that the p-p level of color reference burst is 1V p-p see Figs. 24 & 27.




Fig. 24—Chroma Level

Vertical Detail Level Adjust R3317

1. Place player in "Play" mode.
2. Use stereo alignment disc color bar signal (Segment D).
3. Connect oscilloscope to TP 3404 (Fig. 26).
4. Adjust R3317 so that the pulse level matches before and after transition from vertical equalizing pulses to vertical sync pulses see Figs. 25 & 27.




Fig. 25—Vertical Detail Level

Continued on next page

ELECTRICAL ADJUSTMENTS (continued)

Defect Substitution Level (Delayed Video) Adjust R3304

1. Place player in "Play" mode.
2. Use stereo alignment disc 5 step linearity with defect (Segment I).
3. Connect disc player to TV set. Locate defect (Line No. 130) by rotating R3304 to one end of rotation (Fig. 27).
4. Adjust R3304 for proper substitution to make defect disappear (adjust for best picture).

VCXO Adjust

1. Place player in "Pause" mode.
2. Apply +5V to U3402 Pin 1.
3. Connect DVM from TP 3402 to ground (Fig. 26).
4. Connect 4.7 MΩ resistor from TP 3412 (U3401 Pin 6) to +15V DC source and record voltage V1 measured on DVM at TP 3402 (Fig. 26).
5. Remove 4.7 MΩ resistor end from +15V source and connect it to ground.
6. Record voltage measured on DVM as V2. Remove grounded end of 4.7 MΩ resistor, leave one end connected to TP 3412 (Fig. 26).
7. Using the formula $\Delta F = 3/2 (V1 - V2 - .177)$ kHz, calculate ΔF . (The result should be between 1.90 and 2.52 kHz.)

Example: $\Delta F = 3/2 (8.66V - 7.09V - .177)$ kHz
 $\Delta F = 3/2 (1.393)$ kHz
 $\Delta F = 1.5 \times 1.393$ kHz
 $\Delta F = 2.09$ kHz

NOTE: The voltages shown in solving the formula to determine ΔF are example voltages — actual measured voltages (V1 & V2) will have to be substituted.

8. Calculate high frequency limit $f_H = 1535.625 + \Delta F$ kHz

Example: $f_H = 1535.625$ kHz + 2.09 kHz

9. Calculate low frequency limit. $f_L = 1535.625 - \Delta F$ kHz

Example: $f_L = 1535.625$ kHz - 2.09 kHz

10. Connect frequency counter via X10 probe to TP 3407.

NOTE: Typical capacity of X10 probe is approximately 20-25 pf. A X1 probe (typical capacity of approximately 100 pf) may be used with a 33 pf capacitor placed in series with probe. This will place a load on the VCO of approximately 25 pf.

11. Remove +5V from U3402 Pin 1.
12. Adjust L3403 for 1.534091 ± 100 Hz (Fig. 27).

CAUTION: 4.7 MΩ resistor must be open at one end to make this adjustment.

13. Connect 4.7 MΩ resistor from TP 3412 to +15V source. With player in "Play" mode, release pause mode. Frequency indicated on frequency meter should be ± 100 Hz of previously calculated f_H (EXAMPLE: 1537.715 kHz ± 100 Hz). If not, adjust R3412 to achieve the previously calculated f_H .
14. Remove 4.7 MΩ resistor from +15V source and place player in "Pause" mode. Check that frequency on fre-

quency meter is 1.534091 ± 100 Hz. If not, adjust L3403.

15. Connect 4.7 MΩ resistor from TP 3412 to ground. With player in "Play" mode, release "Pause" mode. Frequency indicated on frequency counter should be ± 100 Hz of previously calculated f_L (Example: 1533.445 kHz ± 100 Hz). If not, adjust L3402 to remove approximately 1/2 of the frequency error and adjust R3412 to remove the remainder.
16. Repeat Steps 13-16 until limits of each are met.
17. Remove 4.7 MΩ resistor from TP 3412.

Phase Detector Gain Adjust R3419

1. Use stereo alignment disc—any signal, place player in "Play" mode.
2. Connect oscilloscope to TP 3408 (Fig. 26).
3. Short TP 3401 to TP 3403 with a clip lead. Short TP 3402 to TP 3403 with a clip lead.
4. Adjust R3419 for 3V p-p waveform at TP 3408 (Fig. 27).
5. Remove shorting clip leads from TP 3401 and TP 3402 to TP 3403.

Audio Demodulator VCO Adjust (716 kHz) (R4111)

1. Place player in "Load" mode.
2. Disconnect interconnect plug P4 (AO).
3. Short the two pins of J4 together.
4. Connect frequency counter via X10 probe (see note) to TP 4008 (Fig. 26).
5. Adjust R4111 for 716 kHz ± 2 kHz (Fig. 27).
6. Remove frequency counter and remove short from the two pins of J4. Reconnect P4.

NOTE: Typical capacity of X10 probe and counter is approximately 20-25 pf. A X1 probe (typical capacity of approximately 100 pf) may be used with a 33 pf capacitor placed in series with probe. This will place a load on the VCO of approximately 25 pf.

Audio Demodulator VCO Adjust (905 kHz) (R4112)

1. Place player in "Load" mode.
2. Disconnect interconnect plug P4 (AO).
3. Short the two pins of J4 together.
4. Connect frequency counter via X10 probe (see note) to TP 4009 (Fig. 26).
5. Adjust R4112 for 905 kHz ± 2 kHz (Fig. 27).
6. Remove frequency counter and remove short from the two pins of J4. Reconnect P4.

NOTE: Typical capacity of X10 probe and counter is approximately 20-25 pf. A X1 probe (typical capacity of approximately 100 pf) may be used with a 33 pf capacitor placed in series with probe. This will place a load on the VCO of approximately 25 pf.

(L+R) Level Adjust (R4127)

1. Place player in "Play" mode.
2. Connect oscilloscope to J4602 (R OUT) Fig. 26.
3. Ground TP 5102.

4. Use stereo alignment disc Segment G (S1: 1020 Hz 50% S2: 1020 Hz 50% out of phase)
5. Adjust R4127 (Fig. 27) to produce 560 ± 20 mV p-p; audio signal at J4602 (R OUT).
6. Remove ground from TP 5102.

(L-R) Level Adjust (R4128)

1. Place player in "Play" mode.
2. Connect oscilloscope to J4602 (R OUT) (Fig. 26).
3. Use stereo alignment disc Segment G. (S1: 1020 Hz 50% S2: 1020 Hz 50% out of phase).
4. Adjust R4128 (Fig. 27) to produce a minimum (null) V p-p at J4602 (R OUT).

TV Audio Level Adjust (R4303)


1. Place player in "Play" mode.
2. Use stereo alignment disc Segment C (S1: 1020 Hz 100%).
3. Connect oscilloscope to TP 3504 (Fig. 26).
4. Adjust R4303 (Fig. 27) to produce 1.2V p-p audio signal at TP 3504.

R. F. Output Channel Oscillator Adjust L3501, L3502

1. With player in "Load" mode, place Channel Switch, S3501, in Channel 3 position. Connect player to TV or 75 ohm load.
2. Connect marker generator (RF input) to TP 3501 and adjust for 61.25 MHz output, Fig. 26.
3. Adjust L3501 for zero beat (Fig. 27).
4. Place Channel Switch, S3501, in Channel 4 position.
5. Connect marker generator (RF input) to TP 3503 and adjust for 67.25 MHz output.
6. Adjust L3502 for zero beat (Fig. 27).

RF Modulator Lower Sideband Trap Adjust L3504, L3503 (Early production instruments only)

1. Turn player power "Off" and connect marker generator output to TP 3501 Fig. 26 marker generator set at 56.75 MHz.
2. Connect quadrupler detector to J3502. Connect oscilloscope (or D. C. Voltmeter) to quadrupler detector and set oscilloscope on DC @ 10 mV/Div.



QUADRUPLER DETECTOR

3. Adjust L3504 (Fig. 27) for null (minimum deflection).
4. Connect marker generator output to TP 3502, marker generator set at 62.75 MHz.
5. Adjust L3503 (Fig. 27) for null (minimum deflection).

NOTE: Do not adjust RF Bandpass Coils L3506 and L3507.

ELECTRICAL ADJUSTMENTS (continued)

4.5 MHz Oscillator Adjust L3509

1. Connect player to TV, player in "Load" mode.
2. Monitor a suitable point in TV IF to pick up 4.5 MHz sound carrier with a frequency counter.
3. Adjust L3509 (Fig. 27) for 4.5 MHz \pm 1 kHz.

Video Modulation Depth Adjust R3402

1. Connect player to TV, player in "Play" mode.
2. Use stereo alignment disc, uniform motion on grey field, S1: 1020 Hz 100% (Segment C).
3. Connect oscilloscope to TP 3504 Fig. 26.
4. Adjust R3402 (Fig. 27) for 1.2 V p-p at TP 3504.

IC VOLTAGE CHARTS

U5101 Player Control μ C

Pin No.	Load	Play	Pause	Unload
1	GND	GND	GND	GND
2	+2.39V	+2.39V	+2.39V	+2.39V
3	+4.86V	+4.86V	+4.86V	+4.86V
4	+4.88V	+4.56V	0V	0V
5	N.C.	N.C.	N.C.	N.C.
6	N.C.	N.C.	N.C.	N.C.
7	+4.81V	+4.81V	+4.81V	+4.81V
8	+4.88V	+4.88V	+4.88V	+4.88V
9	+0.06V	+4.93V	+0.06V	+0.06V
10	+0.06V	+4.93V	+0.06V	+0.06V
11	+4.66V	+4.66V	+4.66V	+4.66V
12	+0.72V	+0.09V	+0.72V	+0.72V
13	See Note 1	See Note 1	See Note 1	See Note 1
14	See Note 1	See Note 1	See Note 1	See Note 1
15	See Note 1	See Note 1	See Note 1	See Note 1
16	See Note 1	See Note 1	See Note 1	See Note 1
17	See Note 1	See Note 1	See Note 1	See Note 1
18	See Note 1	See Note 1	See Note 1	See Note 1
19	See Note 1	See Note 1	See Note 1	See Note 1
20	See Note 4	See Note 4	See Note 4	See Note 4
21	Gnd	Gnd	Gnd	Gnd
22	See Note 4	See Note 4	See Note 4	See Note 4
23	See Note 4	See Note 4	See Note 4	See Note 4
24	See Note 4	See Note 4	See Note 4	See Note 4
25	+4.81V	+4.81V	+4.81V	+4.81V
26	See Note 2	See Note 2	See Note 2	See Note 2
27	See Note 2	See Note 2	See Note 2	See Note 2
28	0V	+4.89V	0V	0V
29	0V	+4.85V	+4.85V	+4.85V
30	See Note 4	See Note 4	See Note 4	See Note 4
31	+0.10V	+0.10V	+0.10V	+0.10V
32	+4.83V	+0.10V	+0.10V	+4.83V
33	0V	+4.84V	+4.84V	+4.84V
34	+0.70V	+0.70V	+0.70V	+0.70V
35	+3.55V	+3.55V	+3.55V	+3.55V
36	0V	+4.87V	+4.87V	+4.87V
37	+4.87V	See Note 3	+4.87V	+4.87V
38	+4.76V	See Note 3	+4.76V	+4.76V
39	+4.76V	See Note 3	+4.76V	+4.76V
40	+4.76V	See Note 3	+4.76V	+4.76V
41	+4.76V	See Note 3	+4.76V	+4.76V
42	+4.87V	+4.87V	+4.87V	+4.87V

N.C.—No Connection

Note 1. Voltage variable—depending upon which element of digital display is illuminated.

3. Adjust R3402 (Fig. 27) clockwise till a buzz is heard in TV audio, then turn counterclockwise to just eliminate the buzz.

Audio Modulation Depth Adjust R4303

1. Place player in "Play" mode.
2. Use stereo alignment disc, uniform motion on grey field, S1: 1020 Hz 100% (Segment C).
3. Connect oscilloscope to TP 3504 Fig. 26.
4. Adjust R4303 (Fig. 27) for 1.2 V p-p at TP 3504.

IC VOLTAGE CHARTS

U 5102 Daxi Buffer μ P

Pin No.	Load	Play	Pause	Unload
1	+2.69V	+2.69V	+2.69V	+2.69V
2	N.C.	N.C.	N.C.	N.C.
3	+2.59V	+2.59V	+2.59V	+2.59V
4	+4.81V	+0.35V	+4.81V	+4.81V
5	See Note 4	See Note 4	See Note 4	See Note 4
6	+2.39V	+2.39V	+2.39V	+2.39V
7	Gnd	Gnd	Gnd	Gnd
8	0V	+0.10V	0V	0V
9	N.C.	N.C.	N.C.	N.C.
10	See Note 4	See Note 4	See Note 4	See Note 4
11	See Note 4	See Note 4	See Note 4	See Note 4
12	N.C.	N.C.	N.C.	N.C.
13	0V	+0.10V	0V	0V
14	+4.95V	+4.95V	+4.95V	+4.95V

U5901 Mechanism Control μ C

Pin No.	Load	Play	Pause	Unload
1	+2.15V	+2.15V	+2.15V	+2.15V
2	+2.58V	+2.58V	+2.58V	+2.58V
3	+4.87V	+4.87V	+4.87V	+4.87V
4	+4.90V	See Note 4	See Note 4	See Note 4
5	+4.90V	See Note 5	See Note 5	See Note 5
6	+0.70V	+0.70V	+0.70V	+0.70V
7	+0.70V	+0.70V	+0.70V	+0.70V
8	+4.84V	+4.68V	+4.68V	+4.84V
9	+4.84V	+4.68V	+4.68V	+4.84V
10	+4.84V	+4.68V	+4.68V	+4.84V
11	+4.84V	+4.68V	+4.68V	+4.84V
12	0V	+4.84V	+4.84V	+4.84V
13	N.C.	N.C.	N.C.	N.C.
14	Gnd	Gnd	Gnd	Gnd
15	N.C.	N.C.	N.C.	N.C.
16	N.C.	N.C.	N.C.	N.C.
17	+4.84V	+0.10V	+0.10V	+4.84V
18	+0.10V	+0.10V	+0.10V	+0.10V

N.C.—No Connection

Note 2. Voltage variable stepper motor control pulses.

Note 3. Voltage controlled by front panel function switches (5600 series). Normally high—momentary low when corresponding function switch is depressed.

IC VOLTAGE CHARTS (continued)

U5901 Mechanism Control μ C (continued)

Pin No.	Load	Play	Pause	Unload
19	+4.84V	+4.84V	+4.84V	+4.84V
20	+4.84V	+4.84V	+4.84V	+4.84V
21	+0.10V	+2.50V	+2.50V	+0.10V
22	+0.10V	+2.50V	+2.50V	+0.10V
23	0V	+4.85V	+4.85V	+4.85V
24	+4.78V	+4.87V	+4.78V	+4.78V
25	+4.78V	0V	0V	0V
26	+4.89V	+4.89V	+4.89V	+4.89V
27	See Note 5	See Note 5	See Note 5	See Note 5
28	+4.89V	+4.89V	+4.89V	+4.89V

U2501 Pulse Interference Corrector (PIC) IC (continued)

Pin No.	Load	Play	Pause	Unload
4	+1.47V	+1.47V	+1.47V	+1.47V
5	+1.47V	+1.47V	+1.47V	+1.47V
6	+1.47V	+1.47V	+1.47V	+1.47V
7	Gnd	Gnd	Gnd	Gnd
8	Gnd	Gnd	Gnd	Gnd
9	N.C.	N.C.	N.C.	N.C.
10	N.C.	N.C.	N.C.	N.C.
11	N.C.	N.C.	N.C.	N.C.
12	+3.64V	+3.64V	+3.64V	+3.64V
13	+11.6V	+11.6V	+11.6V	+11.6V
14	+6.15V	+7.57V	+7.57V	+6.15V

U3101 Sync Detector IC (NLAC)

Pin No.	Load	Play	Pause	Unload
1	+4.69V	+4.77V	+4.69V	+4.69V
2	+3.53V	+3.47V	+3.47V	+3.47V
3	Gnd	Gnd	Gnd	Gnd
4	+1.42V	+1.42V	+1.42V	+1.42V
5	+1.42V	+1.42V	+1.42V	+1.42V

IC VOLTAGE CHARTS (continued)

U3301 ComB Filter/Defect Corrector IC

Pin No.	Load	Play	Pause	Unload
1	+5.05V	+5.05V	+5.05V	+5.05V
2	+5.74V	+5.83V	+5.83J	+5.74V
3	-4.52V	-4.52J	-4.52V	-4.52V
4	+3.89V	+3.89V	+3.89V	+3.89V
5	-4.52V	-4.52V	-4.52V	-4.52V
6	-4.52V	-4.52V	-4.52V	-4.52V
7	-4.52V	-4.52V	-4.52V	-4.52V
8	Gnd	Gnd	Gnd	Gnd
9	+8.86V	+8.86V	+8.86V	+8.86V
10	+3.86V	+3.86V	+3.86V	+3.86V
11	+3.73V	+3.73V	+3.73V	+3.73V
12	+2.57V	+2.57V	+2.57V	+2.57V
13	+2.42V	+2.42V	+2.42V	+2.42V
14	+5.32V	+5.32V	+5.32V	+5.32V
15	+5.18V	+5.18V	+5.18V	+5.18V
16	+14.6V	+14.6V	+14.6V	+14.6V
17	N.C.	N.C.	N.C.	N.C.
18	+5.10V	+5.10V	+5.10V	+5.10V
19	+4.76V	+4.76V	+4.76V	+4.76V
20	+8.50V	+8.50V	+8.50V	+8.50V
21	+7.24V	+7.24V	+7.24V	+7.24V
22	+5.25V	+5.25V	+5.25V	+5.25V

U3402 Video Converter IC (continued)

Pin No.	Load	Play	Pause	Unload
16	+3.24V	+3.24V	+3.24V	+3.24V
17	+3.24V	+3.24V	+3.24V	+3.24V
18	+7.83V	+7.72V	+7.03V	+7.83V
19	+11.7V	+11.7V	+11.7V	+11.7V
20	+1.86V	+1.86V	+1.86V	+1.86V
21	+6.76V	+5.26V	+6.76V	+6.76V
22	+0.66V	+6.80V	+0.66V	+0.66V
23	+1.07V	+0.26V	+1.07V	+1.07V
24	+7.18V	+7.18V	+7.18V	+7.18V

U3501 RF Modulator IC

Pin No.	Load	Play	Pause	Unload
1	+7.18V	+7.18V	+7.18V	+7.18V
2	+7.18V	+7.18V	+7.18V	+7.18V
3	+7.18V	+7.18V	+7.18V	+7.18V
4	+7.18V	+7.18V	+7.18V	+7.18V
5	Gnd	Gnd	Gnd	Gnd

U3401 Armstretcher IC

Pin No.	Load	Play	Pause	Unload
1	+7.97V	+7.97V	+7.24V	+7.97V
2	+7.23V	+7.23V	+7.23V	+7.23V
3	+5.74V	+5.74V	+5.74V	+5.74V
4	+14.6V	+14.6V	+14.6V	+14.6V
5	+7.17V	+7.17V	+7.17V	+7.17V
6	+7.15V	+7.15V	+7.15V	+7.15V
7	+7.65V	+7.65V	+7.65V	+7.65V
8	+6.69V	+6.69V	+6.69V	+6.69V
9	+7.19V	+7.19V	+7.16V	+7.19V
10	+7.16V	+7.16V	+7.16V	+7.16V
11	Gnd	Gnd	Gnd	Gnd
12	+4.89V	+4.89V	+4.89V	+4.89V
13	+4.89V	+4.89V	+4.89V	+4.89V
14	+5.63V	+5.66V	+5.66V	+5.63V

U3402 Video Converter IC

Pin No.	Load	Play	Pause	Unload
1	0V	+4.17V	+1.15V	0V
2	+5.19V	+4.26V	+5.19V	+5.19V
3	+7.17V	+7.17V	+7.17V	+7.17V
4	+3.61V	+3.16V	+3.16V	+3.16V
5	+7.16V	+7.16V	+7.16V	+7.16V
6	+4.44V	+4.44V	+4.44V	+4.44V
7	+2.22V	+2.22V	+2.22V	+2.22V
8	Gnd	Gnd	Gnd	Gnd
9	+3.61V	+3.61V	+3.61V	+3.61V
10	+8.05V	+8.05V	+8.05V	+8.05V
11	+10.5V	+10.5V	+10.5V	+10.5V
12	+7.16V	+7.16V	+7.16V	+7.16V
13	+7.16V	+7.16V	+7.16V	+7.16V
14	+9.42V	+9.42V	+9.42V	+9.42V
15	+9.42V	+9.42V	+9.42V	+9.42V

Note 6. +13.1V channel 3 operation; +1.47V channel 4 operation.

Note 7. +1.47V channel 3 operation; +13.1V channel 4 operation.

IC VOLTAGE CHARTS (continued)

U4102 (L-R) Audio FM Demod IC (905kHz)

Pin No.	Load	Play	Pause	Unload
1	+3.13V	+3.13V	+3.13V	+3.13V
2	+3.13V	+3.13V	+3.13V	+3.13V
3	+3.13V	+3.13V	+3.13V	+3.13V
4	Gnd	Gnd	Gnd	Gnd
5	+6.94V	+6.94V	+6.94V	+6.94V
6	+6.98V	+6.98V	+6.98V	+6.98V
7	+6.28V	+6.28V	+6.28V	+6.28V
8	+4.20V	+4.20V	+4.20V	+4.20V
9	+5.86V	+5.86V	+5.86V	+5.86V
10	Gnd	Gnd	Gnd	Gnd
11	+5.88V	+5.88V	+5.88V	+5.88V
12	+0.85V	+0.85V	+0.85V	+0.75V
13	+2.46V	+5.81V	+5.81V	+2.46V
14	+11.6V	+11.6V	+11.6V	+11.6V
15	+5.27V	+5.27V	+5.27V	+5.27V
16	+5.27V	+5.27V	+5.27V	+5.27V

U4400 Decoder Rectifier IC

Pin No.	Load	Play	Pause	Unload
1	+0.98V	+2.32V	+0.98V	+0.98V
2	+1.30V	+1.37V	+1.30V	+1.30V
3	+1.31V	+1.36V	+1.30V	+1.30V
4	+14.7V	+14.7V	+14.7V	+14.7V
5	+1.31V	+1.37V	+1.31V	+1.31V
6	+1.31V	+1.36V	+1.31V	+1.31V
7	+0.98V	+2.28V	+0.98V	+0.98V
8	+1.00V	+0.95V	+1.00V	+1.00V
9	+1.31V	+1.37V	+1.31V	+1.31V
10	+1.31V	+1.36V	+1.31V	+1.31V
11	Gnd	Gnd	Gnd	Gnd
12	+1.31V	+1.36V	+1.31V	+1.31V
13	+1.31V	+1.36V	+1.31V	+1.31V
14	+1.00V	+0.97V	+1.00V	+1.00V

U4500 Decoder Control IC

Pin No.	Load	Play	Pause	Unload
1	+1.93V	See Note 8	+1.74V	+1.93V
2	+1.43V	See Note 8	+1.43V	+1.43V</


TRANSISTOR VOLTAGE CHART

Q401	E	+3.07V	Q2502	E	+0.34V	Q3201	E	+5.62V	Q3407	E	+7.15V
	B	+3.80V		B	+0.90V		B	+6.29V		B	Varies
	C	+7.84V		C	+14.6V		C	+8.52V		C	+14.7V
Q402	E	+7.08V	Q2503	E	Gnd	Q3202	E	+5.51V	Q3408	E	+7.14V
	B	+7.84V		B	+0V		B	+6.17V		B	Varies
	C	+14.4V		C	+5.84V		C	+11.5V		C	Gnd
Q403	E	+1.08V	Q2504	G	+3.42V	Q3301	E	+4.40V	Q3409	E	Gnd
	B	+2.38V		S	+6.42V		B	+5.03V		B	+0.11V
	C	+7.42V		D	+6.64V		C	+14.6V		C	+4.09V
Q404	E	+1.81V	Q2505	E	+11.6V	Q3303	E	+4.50V	Q3412	E	+3.90V
	B	+2.41V		B	+11.1V		B	+5.16V		B	+4.60V
	C	+14.7V		C	+8.73V		C	+14.6V		C	+5.85V
Q405	A	+7.43V	Q2506	E	+5.94V	Q3304	E	+3.88V	Q3413	E	+5.20V
	G	+12.1V		B	+5.52V		B	+4.49V		B	+5.85V
	K	Gnd		C	+0.18V		C	+14.6V		C	+11.5V
Q2001	E	+22.6V	Q2507	E	Gnd	Q3305	E	+5.65V	Q3501	E	+14.7V
	B	+21.9V		B	+0.18V		B	+5.06V		B	+13.9V
	C	+14.7V		C	+0V		C	Gnd		C	+14.6V
NOT USED SJT 100											
Q2002	E	+23.0V	Q2701	E	+6.46V	Q3306	E	+4.46V	Q4102	E	Gnd
	B	+22.7V		B	+7.13V		B	+5.11V		B	+0.65V
	C	+21.9V		C	+14.7V		C	+11.9V		C	+0.02V
Q2003	E	+2.72V	Q3101	E	+8.83V	Q3401	E	+8.31V	Q4301	E	+7.15V
	B	+3.34V		B	+9.47V		B	+8.98V		B	+7.79V
	C	+21.9V		C	+14.5V		C	+14.6V		C	+14.6V
Q2004	E	+12.1V	Q3102	E	+9.49V	Q3402	E	+3.62V	Q4302	E	+7.15V
	B	+12.7V		B	+8.83V		B	+4.26V		B	+7.79V
	C	+14.1V		C	+4.81V		C	+8.97V		C	+14.6V
Q2005	E	+5.04V	Q3103	E	+4.16V	Q3403	E	+5.61V	Q4501	E	+1.93V
	B	+5.65V		B	+4.82V		B	+6.26V		B	+1.33V
	C	+11.2V		C	+10.3V		C	+9.08V		C	+1.26V
Q2006	E	+4.90V	Q3104	E	+9.60V	Q3404	E	+8.39V	Q5101	E	+3.01V
	B	+5.04V		B	+10.3V		B	+9.04V		B	+4.70V
	C	+5.65V		C	+14.5V		C	+13.9V		C	+2.07V
Q2007	E	+11.9V	Q3105	E	+0.9V	Q3405	E	+7.20V	Q5102	E	+3.01V
	B	+12.1V		B	+1.52V		B	Varies		B	+2.55V
	C	+12.7V		C	+7.72V		C	+14.7V		C	+2.70V
Q2501	E	+6.63V	Q3107	E	+4.72V	Q3406	E	+7.20V	Q5103	E	Gnd
	B	+7.28V		B	+5.28V		B	Varies		B	+0.68V
	C	+12.9V		C	+7.80V		C	Gnd		C	+0.02V

TRANSISTOR VOLTAGE CHART (continued)

Q5104	E	Gnd	Q5115	E	Gnd	NORM	FWD/ RUN	STOP	RUN
	B	Steps Hi-Lo		B	+0.74V			Q5931	E +23.5V +22.6V
	C	Steps Hi-Lo		C	+0.02V				B +23.5V +22.6V
								C 0V +1.58V	
Q5105	E	Steps Hi-Lo	Q5116	E	Gnd	NORM	FWD/ RUN	STOP	RUN
	B	Steps Hi-Lo		B	+0.02V			Q5932	E +0.05V +0.10V
	C	Steps Hi-Lo		C	+4.87V				B +0.25V +0.33V
								C +23.4V +21.3V	
Q5106	E	+22.9V	Q5301	E	Gnd	NORM	FWD/ RUN	STOP	RUN
	B	+22.8V		B	+0.70V			Q5933	E 0V +0.02V
	C	Steps Hi-Lo		C	+0.02V				B +0.05V +0.10V
								C +0.24V +6.35V	
Q5107	E	Gnd	Q5302	E	Gnd	NORM	FWD/ RUN	STOP	RUN
	B	Steps Hi-Lo		B	+0.66V			Q5941	E +23.4V +22.6V
	C	Steps Hi-Lo		C	+0.06V				B +23.4V +22.6V
								C 0V +1.58V	
Q5108	E	+3.27V	Q5303	E	+4.74V	NORM	REV/ RUN	STOP	RUN
	B	+3.91V		B	+5.12V			Q5942	E +0.02V +0.87V
	C	+3.84V		C	+22.5V				B +0.02V +0.87V
								C +22.8V +18.8V	
Q5109	E	+13.1V	Q5304	E	+4.75V	NORM	MOMENT SWITCH	STOP	RUN
	B	+12.3V		B	+5.12V			Q5943	E 0V +0.02V
	C	+13.0V		C	Gnd				B +0.05V +0.10V
								C +0.24V +6.30V	
Q5110	E	+3.89V	Q5305	E	+4.28V	NORM	MOMENT SWITCH	STOP	RUN
	B	+4.50V		B	+4.75V			Q5944	E 0V +0.02V
	C	+8.71V		C	+22.5V				B +0.05V +0.10V
								C +0.24V +6.30V	
Q5111	E	Steps Hi-Lo	Q5306	E	+4.28V	STOP	RUN	STOP	RUN
	B	Steps Hi-Lo		B	+4.75V			Q5945	E 0V +0.02V
	C	+22.0v		C	Gnd				B +0.05V +0.10V
								C +0.24V +6.30V	
Q5112	E	+22.0V	Q5901	E	Gnd	STOP	RUN	STOP	RUN
	B	Steps Hi-Lo		B	+0.70V			Q5946	E +0.05V +0.10V
	C	Steps Hi-Lo		C	+0.75V				B +0.25V +0.33V
					0V			C +23.4V +21.3V	
Q5113	E	+4.90V	Q5902	E	+4.90V	STOP	RUN	STOP	RUN
	B	+4.55V		B	+0.02V			Q5947	E 0V +0.02V
	C	+3.01V		C	0V				B +0.05V +0.10V
								C +0.24V +6.30V	
Q5114	E	+4.90V	Q5903	E	+0.02V	STOP	RUN	STOP	RUN
	B	+4.58V		B	+0.09V			Q5948	E 0V +0.02V
	C	+3.90V		C	+22.6V				B +0.05V +0.10V
								C +0.24V +6.50V	

NOTE: Voltages measured with DVM—Player in "PLAY" mode unless otherwise indicated.




NOTE: L3503 and L3504 in RF modulator not used all versions.

Fig. 26—Test Point and Active Device Location

TEST POINT AND ACTIVE DEVICE IDENTIFICATION

TEST POINTS	ACTIVE DEVICES	ACTIVE DEVICES (Continued)
TP2001 + 22VDC	Q2001 Regulator	Q5302 Forward Ramp Switch
TP2002 + 10VDC	Q2002 Current Limiter	Q5303 Kick Pulse Driver
TP2003 + 5.0V Ref	Q2003 Driver	Q5304 Kick Pulse Driver
TP2004 + 15VDC (In 3400 Area)	Q2004 Regulator	Q5305 Kick Pulse Output
TP2005 + 5VDC	Q2005 Regulator	Q5306 Kick Pulse Output
TP2006 + 12VDC (In 2500 Area)	Q2006 Current Limiter	Q5901 Reverse Function Switch
TP2501 FM In	Q2007 Current Limiter	Q5902 Function Drive Reverse
TP2502 Detector Out	Q2501 RF Amplifier	Q5903 Forward Function Switch
TP2503 Defect Input	Q2502 Output Detector/Switch	Q5904 Function Drive Forward
TP3101 Anlac Setup	Q2503 Output Detector/Switch	Q5905 Function Motor Output
TP3102 Arm Input	Q2504 Gain Control	Forward
TP3201 5.3MHz VCO	Q2505 AGC Amplifier	Q5906 Function Motor Output
TP3202 Video Input to U3301	Q2506 Sync Stripper	Reverse
TP3301 Vertical Detail Out	Q2507 Clamp	Q5907 Pause Line Buffer
TP3302 Luminance Out	Q2701*	Q5921 Current Source Switch
TP3303 Vertical Detail	Q3101 N-Lac Buffer	Q5922 Drive Amplifier
TP3304 1.53MHz Chroma	Q3102 N-Lac Amplifier	Q5923 Turntable Motor Driver B
TP3401 VCXO Setup	Q3103 N-Lac Amplifier	Q5931 Current Source Switch
TP3402 VCXO Input	Q3104 N-Lac Output Driver	Q5932 Drive Amplifier
TP3403 + 7VDC Ref	Q3105 716KHz Amplifier	Q5933 Turntable Motor Driver A
TP3404 Luminance Input	Q3107 Control Amplifier	Q5941 Current Source Switch
TP3405 1.53MHz Clock	Q3201 Phase Corrector	Q5942 Drive Amplifier
TP3406 3.58MHz Oscillator	Q3202 Video Buffer	Q5943 Turntable Motor Driver D
TP3407 1.53MHz Clock Buffered	Q3301 Delayed Video Drive	Q5951 Current Source Switch
TP3408 Phase Detector Output	Q3303 Vertical Detail Buffer	Q5952 Drive Amplifier
TP3409 5.11MHz Oscillator	Q3304 Chroma Driver	Q5953 Turntable Motor Driver C
TP3410 Video Input to Modulator	Q3305 Chroma Buffer	U2001 Quad Operational Amplifier
TP3411 Armstretcher Setup	Q3306 Luma Buffer	U2501 Sync Detector
TP3501 Channel 3 Output	Q3401 Video Buffer	U3101 Sync Detector
TP3502 Channel 4 Output	Q3402 Video Amplifier	U3201 Video FM Demodulator
TP3503 4.5MHz Input	Q3403 Clock Phase Shifter	U3301 Comb Filter/Defect Corrector
TP3504 Audio Input	Q3404 Clock Buffer	U3401 Armstretcher Drive
TP4001 Left Plus Right Output	Q3405 Transducer Driver	U3402 Video Converter
TP4002* Left Minus Right Output	Q3406 Transducer Driver	U3501 RF Modulator
TP4003* Rectified Output	Q3407 Transducer Driver	U4101 Audio Demodulator
TP4006* Left Matrix Output	Q3408 Transducer Driver	U4102* Audio Demodulator
TP4007* Right Matrix Output	Q3409 Video Blanker	U4200 Track/Hold Mute
TP4008 716KHz VCO	Q3412 Noise Coring Amplifier	U4300* Audio Matrix & Buffer
TP4009* 905KHz VCO	Q3413 Noise Coring Buffer	U4400* Decoder Rectifier
TP4010* Decoder Disable	Q3501 Bias Switch	U4500* Decoder Control
TP4011 + 7.5VDC Ref	Q4102* Decoder Defeat	U4600* Decoder Amplifier
TP4012* + 1.4VDC Ref	Q4301* Left Channel Buffer	U5101 Player Control
TP5101 Audio Channel A Mute	Q4302* Right Channel Buffer	Microcomputer
TP5102 Audio Channel B Mute	Q4501* Current Source	U5102 Daxi Buffer
TP5103 Squelch	Q5101 Least Significant Digit Driver	U5901 Mechanism Microcomputer
TP5901 Turntable Motor Drive	Q5102 Most Significant Digit Driver	U5902 Turntable Drive
Voltage B	Q5103 Daxi Status Inverter	VR2001 5.8V Zener
TP5902 Turntable Motor Drive	Q5104 Stepper Output B	VR3301 9.1V Zener
Voltage A	Q5105 Stepper Drive A	VR5101 2.85V Zener
TP5903 Turntable Motor Drive	Q5106 Stepper Output A	*Not Used on Model SJT100.
Current B	Q5107 Stepper Output D	
TP5904 Turntable Motor Drive	Q5108 Lifter Drive	
Current A	Q5109 Lifter Output	
TP5905 Turntable Motor Drive	Q5110 Vertical Detail Driver	
Voltage D	Q5111 Stepper Drive C	
TP5906 Turntable Motor Drive	Q5112 Stepper Output C	
Voltage C	Q5113 LED Display Select	
TP5907 Turntable Motor Drive	Q5114 Discrete LED Select	
Current D	Q5115 Low Voltage Detector	
TP5908 Turntable Motor Drive	Q5116 Reset Switch	
Current C	Q5301 Reverse Ramp Switch	

WAVEFORMS (Continued)



SCHEMATIC DIAGRAM






Fig. 31—Pickup Arm Electronics


WAVEFORMS (Continued)




(31) 10mS/Div. 4V p-p




(32) 10mS/Div. .2V p-p




(33) 10mS/Div. .22V p-p




(34) 10mS/Div. .2V p-p




(35) 10mS/Div. .2V p-p




(36) 10mS/Div. 1.5V p-p




(37) 10mS/Div. 1.5V p-p




(38) 10mS/Div. 1.5V p-p




(39) 10mS/Div. 1.5V p-p




(40) 5mS/Div. 5V p-p




(41) 5mS/Div. 5V p-p



(42) 5mS/Div. 5V p-p



(43) 1mS/Div. 5V p-p



(44) 5mS/Div. 5V p-p

ELECTRICAL ADJUSTMENTS






Fig. 27—Adjustment Points

 μ C FUNCTIONAL BLOCK DIAGRAMFig. 28—U5101 Player Control μ CFig. 29—U5901 Mechanism Control μ C




Fig. 30—Interconnect Wiring Diagram SJT 100/200/300

SCHEMATIC DIAGRAM






Fig. 31—Pickup Arm Electronics

SCHEMATIC DIAGRAM


SCHEMATIC DIAGRAM




SCHEMATIC DIAGRAM



SCHEMATIC DIAGRAM



SCHEMATIC DIAGRAM



SCHEMATIC DIAGRAM

SCHEMATIC DIAGRAM




Fig. 34a—Stereo Audio Electronics SJT 200/300

SCHMATIC DIAGRAM




Fig. 34b—Monaural Audio Electronics SJT 100




Fig. 35—Power Supply Electronics





Fig. 36—PW Master Circuit Board Assembly

PW MASTER CIRCUIT BOARD

Component Location Guide



8PF3101	7D	C3309	8A	C3522	2D	C5128	1A	CR5117	4B	Q2005	1A	Q5951	5D	R3131	8D	R3433	5B	R4111	7E	R4606	6F	R5305	1F	R5977	1D	VSF	3A
8PF4101	8F	C3310	8A	C3523	2F	C5129	3B	CR5301	2F	Q2006	1B	Q5952	5D	R3134	8D	R3434	6C	R4112	6D	R4607	6F	R5306	2F	U2001	1E	VSR	3A
8PF4102	7E	C3311	8A	C3524	3E	C5130	3B	CR5302	2F	Q2007	1E	Q5953	5D	R3135	7E	R3435	6B	R4113	8E	R4608	6F	R5307	2E	U2501	6D		
C2001	1D	C3312	7B	C3525	3D	C5131	2A	CR5901	1E	Q2501	7D	R2001	1E	R3201	7D	R3436	5A	R4114	6E	R4609	6F	R5308	1F	U3101	7E		
C2002	4A	C3313	7B	C3526	3E	C5132	2F	CR5902	1D	Q2502	7D	R2002	1E	R3202	8D	R3437	6A	R4115	8F	R4610	6F	R5309	1F	U3201	8C	TP2001	1E
C2003	1E	C3314	8B	C3527	2E	C5132	2F	CR5903	1D	Q2503	7C	R2003	1E	R3203	7C	R3438	5A	R4116	6D	R4611	6F	R5310	2F	U3301	8B	TP2002	1A
C2004	1F	C3315	7B	C3528	4E	C5133	1F	CR5904	1D	Q2504	6D	R2004	1E	R3204	8D	R3439	5A	R4117	8F	R4612	6F	R5311	2C	U3401	4A	TP2003	1E
C2005	1C	C3316	7A	C3530	3F	C5134	1F	CR5905	2D	Q2505	7D	R2005	1E	R3205	8C	R3440	5A	R4118	6E	R4613	6F	R5312	2F	U3402	6A	TP2004	5B
C2501	7D	C3317	7B	C3532	3E	C5136	1F	CR5906	1D	Q2506	7C	R2006	1E	R3206	8D	R3441	5A	R4121	7E	R4614	6F	R5313	1F	U3501	3E	TP2005	2C
C2503	6C	C3318	8B	C3533	3E	C5137	2C	CR5907	1E	Q2507	7C	R2007	2E	R3207	8C	R3442	4A	R4122	6D	R4615	7F	R5314	2F	U4101	7F	TP2006	6C
C2504	6D	C3319	8B	C4001	7F	C5138	1C	CR5921	4C	Q2701	4E	R2008	1E	R3208	8C	R3443	4A	R4123	7E	R4616	6F	R5315	2E	U4102	6E	TP2501	7D
C2505	6D	C3320	7B	C4002	7F	C5139	1C	CR5922	3C	Q3101	6E	R2009	1E	R3209	8D	R3444	5A	R4124	6D	R4619	6F	R5301	1C	U4200	5E	TP2502	6D
C2506	6C	C3321	8A	C4003	5F	C5140	1C	CR5923	4D	Q3102	8E	R2010	1E	R3210	8D	R3445	5A	R4125	7E	R4620	5F	R5302	2E	U4300	4E	TP2503	7C
C2507	6C	C3322	8A	C4004	5F	C5141	1C	CR5931	4C	Q3103	8E	R2011	1D	R3211	8C	R3446	4A	R4126	6E	R5101	1A	R5903	1E	U4400	4F	TP3101	7E
C2508	7D	C3323	7B	C4107	8F	C5142	3C	CR5906	3C	Q3104	8E	R2012	1E	R3212	8C	R3447	4A	R4127	7E	R5102	3B	R5904	1D	U4500	5F	TP3102	8E
C2509	7D	C3324	7B	C4108	6E	C5143	3C	CR5933	4D	Q3105	7D	R2013	1E	R3213	6C	R3448	4A	R4128	6D	R5103	3B	R5905	2D	U4600	6F	TP3201	7C
C2510	7D	C3325	7B	C4109	8F	C5144	5C	CR5941	5C	Q3107	8D	R2014	1E	R3214	8C	R3449	4A	R4129	7F	R5104	3A	R5906	1D	U5101	2A	TP3202	8C
C2511	6D	C3326	7B	C4110	6E	C5145	2D	CR5942	3C	Q3201	8D	R2015	1E	R3215	8C	R3450	6A	R4130	6E	R5105	1B	R5907	1C	U5102	3A	TP3301	7B
C2512	6D	C3327	7A	C4111	8F	C5146	5D	CR5943	5D	Q3202	8C	R2016	1E	R3216	8C	R3451	6B	R4136	5E	R5106	1B	R5908	1C	U5901	1C	TP3302	7B
C2513	6C	C3328	8A	C4112	7E	C5147	2D	CR5951	5C	Q3301	7A	R2017	1E	R3217	7D	R3452	5A	R4140	6E	R5107	1B	R5909	1C	U5902	4D	TP3303	7B
C2514	6C	C3329	8A	C4113	8F	C5148	1D	CR5952	3C	Q3303	8C	R2018	1E	R3218	8C	R3453	5B	R4141	7F	R5108	1B	R5910	1C	VR2001	1F	TP3304	6A
C2515	6D	C3330	7B	C4114	7E	C5149	3C	CR5953	5D	Q3304	7A	R2019	1F	R3219	8D	R3454	5B	R4143	7F	R5109	1B	R5911	3C	VR3301	8A	TP3401	5A
C2516	6D	C3331	8B	C4117	7F	C5150	3C	CR5954	5C	Q3305	8B	R2020	1F	R3220	8C	R3455	5B	R4144	6E	R5110	1B	R5913	2D	TP3402	5A		
C2517	7D	C3333	7A	C4118	6E	C5151	3D	E3201	7C	Q3306	8B	R2021	1A	R3221	7C	R3456	6B	R4145	7F	R5111	1B	R5914	2D	Y3401	6A	TP3403	6A
C2701	4E	C3335	7A	C4119	7E	C5152	3C	E3301	7A	Q3401	5B	R2022	4B	R3222	7C	R3457	6C	R4146	6E	R5112	2B	R5915	1E	Y5901	1C	TP3404	6A
C2702	4E	C3336	7B	C4120	6D	C5153	2D	E3302	7A	Q3402	5B	R2023	1A	R3303	7A	R3458	6C	R4147	5D	R5113	2B	R5916	1D	TP3405	7A		
C2703	4E	C3401	6A	C4121	7F	C5154	1D	E3303	7B	Q3403	6B	R2024	1A	R3304	7A	R3459	6C	R4201	6E	R5114	2B	R5917	2D	STAKES	TP3406	6A	
C2705	4F	C3402	6A	C4122	6E	C5155	1D	E3501	4F	Q3404	6B	R2025	1E	R3307	7A	R3460	6C	R4202	5D	R5115	1B	R5919	1C	A1	2F	TP3407	6B
C3101	8F	C3403	6A	C4125	7F	C5156	3C	E3502	2E	Q3405	5A	R2051	7D	R3308	8A	R3461	5B	R4203	5E	R5116	3B	R5920	1C	ANX	2E	TP3408	6B
C3102	8E	C3404	6B	C4126	6E	C5157	4D	E3503	3D	Q3406	5A	R2052	7D	R3309	7B	R3462	6B	R4204	5E	R5117	3B	R5921	2C	AO	7E	TP3409	

STAR or SHADING (*)
See PRODUCT SAFETY NOTICE
on page 2 of this Service Data.

SCHEMATIC DIAGRAM/CIRCUIT BOARDS**NOTES:**

1. ALL RESISTORS 1/4W UNLESS OTHERWISE SPECIFIED.
2. RESISTANCE VALUES IN OHMS, K=1000.
3. ALL RESISTORS ARE 5% TOLERANCE, UNLESS OTHERWISE SPECIFIED.




Fig. 37—CRK 34 Remote Transmitter Schematic SJT 300




Fig. 38—PW 1000 Circuit Board Assembly (SJT 300)




Fig. 39—PW 1100 Circuit Board Assembly (SJT 300)

STAR or SHADING (*)
See PRODUCT SAFETY NOTICE
on page 2 of this Service Data.




SCHEMATIC DIAGRAM

Fig. 40—Remote Preamp/Decoder Schematic (SJT 300)

CIRCUIT BOARDS



NOTE: Add 900 Series Prefix to Item Numbers

Fig. 41—PW 900 Circuit Board Assembly (SJT 300)





Fig. 42—PW Arm Interconnect Circuit Board Assembly



NOTE: Add 400 Series Prefix to Item Numbers

Fig. 43—PW 400 Circuit Board Assembly






Fig. 44—PW 1700 Circuit Board Assembly



NOTE: Add 600 Series Prefix to Item Numbers

Fig. 45—PW 600 Circuit Board Assembly

BLOCK DIAGRAM



Functional Block Diagram

BLOCK DIAGRAM

BLOCK DIAGRAM





Fig. 46—Functional Block Diagram SJT 100/200/300

Functional Block Diagram

59


1983 SJT 100/

1983 SJT 100/200/300



NOTE:


Fig. 41-PW



NOTE:

Fig. 43

EXPLODED VIEW






Fig. 47—Cabinet and Player Mechanism




Fig. 48—Arm Assembly SJT 100/200




Fig. 49—Arm Assembly SJT 300




Fig. 50—Arm Drive Assembly SJT 100/200

REPLACEMENT PARTS

BEFORE REPLACING PARTS, READ THE FOLLOWING:

RCA-Approved Substitute Stock Numbers—Before ordering stock numbers in this parts list, look for an RCA-approved substitute stock number in the current **RCA Distributor & Special Products Price Schedule**. This will minimize your service time and avoid ordering parts you already have in stock.

See your RCA Distributor for Replacement Parts and Accessories.

Warranty Status of Assemblies and Parts—The warranty status of some assemblies and parts are indicated by one of the following Warranty Status Codes:

• Complete assembly not eligible for warranty exchange or replacement.
† Eligible for warranty exchange for new or rebuilt unit.

‡ Complete assembly eligible for warranty replacement with new or rebuilt unit.

.....AVOID REPLACEMENT PART ERRORS.....
File supplements and addendums immediately upon receipt, and consult the parts lists in them before ordering parts.

NOTE: For complete coverage of all parts and assemblies used in instruments equipped with the chassis series to which this service data relates, consult the following publications.

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
SJT100/200/300			

ELECTRICAL ASSEMBLIES & COMPONENTS

157928	2812587-501	• CIRCUIT, AC INPUT PW600
157925	2816408-501	• CIRCUIT, ARM INTERCONNECT SJT100
157926	2816408-502	• CIRCUIT, ARM INTERCONNECT SJT200/300
158005	2816404-501	• CIRCUIT, DISPLAY SJ200/300
157989	2816404-502	• CIRCUIT, DISPLAY SJT100
157924	2812585-501	• CIRCUIT, PICKUP PREAMP PW400
155877	2812595-501	‡ CIRCUIT, RESONATOR SJT100/200
155878	2812595-502	‡ CIRCUIT, RESONATOR SJT300

ELECTRICAL COMPONENTS

B1	156528	2816407-504	‡ MOTOR TURNTABLE DRIVE (CIRCUIT BOARD COMPLETE)
B2	154243	2872666-021	MOTOR ARM DRIVE
B3	155879	2816456-504	MOTOR FUNCTION DRIVE
BPF3101	157184	2861041-001	FILTER BAND-PASS
BPF4101	157184	2861041-001	FILTER BAND-PASS
BPF4102	157183	2861041-002	FILTER BAND-PASS SJT200/300
C1	145896	1491415-50R	CAPCD 4700PF M 50V
C401	143881	2841254-41M	CAPCD 2200PF M Z5P 50V
C402	147971	2841255-31N	CAPCD .01UF M Z5T 50V
C403	148057	2841253-92M	CAPCD 1000PF K Z5P 50V
C404	141868	2841273-163	CAP LYTC 1UF M 85C 50V
C405	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C406	146365	2841273-552	CAP LYTC 4.7UF M 85C 25V
C407	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C408	148057	2841253-92M	CAPCD 1000PF K Z5P 50V
C409	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C410	148057	2841253-92M	CAPCD 1000PF K Z5P 50V
C601	157931	2870697-110	* CAPCD 600PF M Z5T 1400V
C602	157931	2870697-110	* CAPCD 600PF M Z5T 1400V
C603	157930	2841255-61N	CAPCD .015UF M Z5T 50V
C604	157930	2841255-61N	CAPCD .015UF M Z5T 50V
C605	157930	2841255-61N	CAPCD .015UF M Z5T 50V
C606	153654	1490303-451	CAP LYTC 3300UF R 35V
C607	149152	1490303-341	CAP LYTC 2200UF R 25V
C2001	146216	2840363-342	CAP LYTC 2200UF 25V
C2002	112969	1490939-703	CAPCD .1UF Z Y5T 50V
C2003	153176	2871335-016	CAP POLY .33UF M 100V
C2004	143967	2841254-81M	CAPCD 4700PF M Z5P 50V
C2005	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C2051	147036	2840395-30N	CAPCD .010UF M Z5R 50V
C2053	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C2054	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C2055	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C2056	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C2057	134939	2841255-91M	CAPCD 1000PF M Z5P 50V
C2225	143871	2841255-50R	CAPCD .047UF Z Z5V 50V

Continued on next page

REPLACEMENT PARTS

Replacement Parts Continued (See Product Safety Note on first page of this parts list)

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION	SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
C3226	157205	2841250-82A	CAPCD 4.7PF K NPO 50V	C3521	145741	2841254-41N	CAPCD 2200PF M Z5T 50V
C3227	143867	2841252-23A	CAPCD 47PF J NPO 50V	C3522	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C3228	143879	2841253-91M	CAPCD 1000PF M Z5P 50V	C3523	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3229	157204	2841250-92A	CAPCD 5.6PF K NPO 50V	C3524	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3301	154336	2871335-083	CAP POLY .47UF K 100V	C3525	143866	2841251-83A	CAPCD 27PF J NPO 50V
C3302	143967	2841254-81M	CAPCD 4700PF M Z5P 50V	C3526	135375	2841253-93M	CAPCD 1000PF J SL 50V
C3303	148057	2840393-92M	CAPCT 1000PF K Z5P 50V	C3527	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3304	149161	2841274-243	CAP LYTC 15UF M 85C 25V	C3528	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3307	134939	2841255-50R	CAPCD .047UF Z Z5V 50V	C3530	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3308	153925	2872860-125	CAP POLY 0.1UF K 50V	C3532	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C3309	146418	2841252-93A	CAPCD 180PF J NPO 50V	C4001	149203	2841275-143	CAP LYTC 100UF M 85C 25V
C3310	112969	1490939-703	CAPCD .1UF Z Y5T 50V	C4002	134939	2841255-50R	CAP LYTC 100UF M 85C 25V
C3311	143874	2841252-83H	CAPCD 150PF J N750 50V	C4003	149203	2841275-143	CAP LYTC 100UF M 85C 25V
C3312	135452	2841253-13H	CAPCD 220PF J N750 50V	C4004	134939	2841255-50R	CAPCD .047UF Z Z5V 50V SJT200/300
C3313	146210	2841273-553	CAP LYTC 4.7UF M 85C 50V	C4107	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C3314	134939	2841255-50R	CAPCD .047UF Z Z5V 50V	C4108	134939	2841255-50R	CAPCD .047UF Z Z5V 50V SJT200/300
C3315	143874	2841252-83H	CAPCD 150PF J N750 50V	C4109	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C3316	147036	2840395-30N	CAPCT .010UF M Z5R 50V	C4110	134939	2841255-50R	CAPCD .047UF Z Z5V 50V SJT200/300
C3317	146210	2841273-553	CAP LYTC 4.7UF M 85C 50V	C4111	149188	2871335-129	CAP POLY .015UF J 100V
C3318	147635	2841262-005	CAPCD 130PF J NPO 50V	C4112	149163	2872860-217	CAP POLY .022UF J 50V SJT200/300
C3319	135452	2841253-13H	CAPCD 220PF J N750 50V	C4113	149188	2872860-215	CAP POLY .015UF J 50V
C3320	157211	2872860-205	CAP POLY .022UF J 50V	C4114	149163	2872860-217	CAP POLY .022UF J 50V SJT200/300
C3321	146210	2841273-553	CAP LYTC 4.7UF M 85C 50V	C4117	146536	2841273-362	CAP LYTC 2.2UF N 85C 50V
C3322	148057	2840393-92M	CAPCD 1000PF K Z5P 50V	C4118	146536	2841273-362	CAP LYTC 2.2UF N 85C 50V
C3323	146418	2841252-93A	CAPCD 180PF J NPO 50V	C4121	153576	2841253-53H	CAPCD 470PF J N750 50V
C3324	134939	2841255-50R	CAPCD .047UF Z Z5V 50V	C4122	157197	2841253-41H	CAPCD 390PF M N750 50V
C3325	143879	2841253-13H	CAPCD 220PF J N750 50V	C4125	143967	2841254-81M	CAPCD 4700PF M Z5P 50V
C3326	143874	2841252-83H	CAPCD 150PF J N750 50V	C4126	143967	2841254-81M	CAPCD 4700PF M Z5P 50V

REPLACEMENT PARTS

Replacement Parts Continued (See Product Safety Note on first page of this parts list)

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
------------	-----------	-------------	-------------

C5103	157199	2841251-73A	CAPCD 22PF J NPO 50V
C5104	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5105	146256	2841274-143	CAP LYTC 10UF M 25V
C5106	149204	2841274-442	CAP LYTC 33UF N 85C 25V
C5107	157207	2872860-023	CAP POLY .067UF M 50V
C5108	141868	2841273-163	CAP LYTC 1UF M 85C 50V
C5109	149203	2841275-143	CAP LYTC 100UF M 85C 25V
C5110	149203	2841275-143	CAP LYTC 100UF M 85C 25V
C5111	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5112	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5113	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5114	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5115	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5116	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5117	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5119	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5120	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5121	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5122	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5123	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5124	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5125	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5126	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5127	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C5128	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5129	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C5130	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C5131	147971	2841255-31M	CAPCD .01UF M Z5P 50V SJT300
C5301	153925	2872860-125	CAP POLY 0.1UF K 50V
C5302	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5303	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C5304	143550	2841274-543	CAP LYTC 47UF M Z5U
C5306	143878	2841253-62M	CAPCD 560PF K Z5P 50V
C5901	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5902	132174	1474578-007	CAP TRIM 11PF NPO 500V
C5903	146768	2841251-53A	CAPCD 15PF J NPO 50V
C5904	145676	2841252-43A	CAPCD 68PF J NPO 50V
C5905	146768	2841251-53A	CAPCD 15PF J NPO 50V
C5906	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5907	143879	2841253-91M	CAPCD 1000PF M Z5P 50V
C5908	147036	2840395-30N	CAPCT .010UF M Z5R 50V
C5909	147036	2840395-30N	CAPCT .010UF M Z5R 50V
C5910	146256	2841274-143	CAP LYTC 10UF M 25V
C5911	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5912	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5913	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5914	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5915	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5916	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5917	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5918	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5919	147971	2841255-31M	CAPCD .01UF M Z5P 50V
C5920	149204	2841274-442	CAP LYTC 33UF N 85C 25V
C5921	157196	2841255-41L	CAPCD .022UF M Y5R 50V
C5922	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5931	157196	2841255-41L	CAPCD .022UF M Y5R 50V
C5941	157196	2841255-41L	CAPCD .022UF M Y5R 50V
C5951	157196	2841255-41L	CAPCD .022UF M Y5R 50V
DS1701	149020	2840935-001	LED DISPLAY
CR101	119597	1471872-006	DIODE
CR601	147015	99203-206	DIODE
CR602	147015	99203-206	DIODE
CR603	147015	99203-206	DIODE
CR604	147015	99203-206	DIODE
CR605	147015	99203-206	DIODE
CR606	147015	99203-206	DIODE
CR607	147015	99203-206	DIODE
CR608	147015	99203-206	DIODE
CR609	119597	1471872-006	DIODE
CR610	119597	1471872-006	DIODE
CR611	119597	1471872-006	DIODE
CR1701	157637	1466679-013	DIODE LED SIDE 1
CR1702	157637	1466679-013	DIODE LED SIDE 2
CR1703	157637	1466679-013	DIODE LED AUD A SJT200/300
CR1704	157637	1466679-013	DIODE LED AUD B SJT200/300
CR1705	157637	1466679-013	DIODE LED STEREO SJT200/300
CR2009	119597	1471872-010	DIODE
CR2501	119597	1471872-010	DIODE
CR3101	119597	1471872-010	DIODE
CR3102	119597	1471872-010	DIODE
CR3103	119597	1471872-010	DIODE
CR3104	119597	1471872-010	DIODE
CR3105	119597	1471872-010	DIODE
CR3106	119597	1471872-010	DIODE
CR3107	119597	1471872-010	DIODE
CR3108	119597	1471872-010	DIODE
CR3109	119597	1471872-010	DIODE
CR3110	119597	1471872-010	DIODE
CR3111	119597	1471872-010	DIODE
CR3112	119597	1471872-010	DIODE
CR3113	119597	1471872-010	DIODE
CR3114	119597	1471872-010	DIODE
CR3115	119597	1471872-010	DIODE
CR3116	119597	1471872-010	DIODE
CR3117	119597	1471872-010	DIODE
CR3118	119597	1471872-010	DIODE
CR3119	119597	1471872-010	DIODE
CR3120	119597	1471872-010	DIODE
CR3121	119597	1471872-010	DIODE
CR3122	119597	1471872-010	DIODE
CR3123	119597	1471872-010	DIODE
CR3124	119597	1471872-010	DIODE
CR3125	119597	1471872-010	DIODE
CR3126	119597	1471872-010	DIODE
CR3127	119597	1471872-010	DIODE
CR3128	119597	1471872-010	DIODE
CR3129	119597	1471872-010	DIODE
CR3130	119597	1471872-010	DIODE
CR3131	119597	1471872-010	DIODE
CR3132	119597	1471872-010	DIODE
CR3133	119597	1471872-010	DIODE
CR3134	119597	1471872-010	DIODE
CR3135	119597	1471872-010	DIODE
CR3136	119597	1471872-010	DIODE
CR3137	119597	1471872-010	DIODE
CR3138	119597	1471872-010	DIODE
CR3139	119597	1471872-010	DIODE
CR3140	119597	1471872-010	DIODE
CR3141	119597	1471872-010	DIODE
CR3142	119597	1471872-010	DIODE
CR3143	119597	1471872-010	DIODE
CR3144	119597	1471872-010	DIODE
CR3145	119597	1471872-010	DIODE
CR3146	119597	1471872-010	DIODE
CR3147	119597	1471872-010	DIODE
CR3148	119597	1471872-010	DIODE
CR3149	119597	1471872-010	DIODE
CR3150	119597	1471872-010	DIODE
CR3151	119597	1471872-010	DIODE
CR3152	119597	1471872-010	DIODE
CR3153	119597	1471872-010	DIODE
CR3154	119597	1471872-010	DIODE
CR3155	119597	1471872-010	DIODE
CR3156	119597	1471872-010	DIODE
CR3157	119597	14718	

REPLACEMENT PARTS

Replacement Parts Continued (See Product Safety Note on first page of this parts list)

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION	SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
R2008	157212	990401-430	RES MF 1/4W 1% 20K	R4311	829320	993218-728	RES CF 1/4W 2% 20K SJT200/300
R2009	157213	990401-401	RES MF 1/4W 1% 10K	R4312	157333	2815583-728	RES CF 1/8W 2% 20K SJT200/300
R2010	829068	993113-197	* RES MFFF 1/4W 5% 68R	R4317	157333	2815583-728	RES CF 1/8W 2% 20K SJT200/300
R2013	830A68	993273-345	* RES CFFF 1/2W 5% 6.8R	R4503	157333	2815583-708	RES CF 1/8W 2% 3K SJT200/300
R2014	830033	993290-189	* RES MFFF 1/2W 5% 33R	R4505	157333	2815583-752	RES CF 1/8W 2% 200K SJT200/300
R2016	157336	2815583-721	RES CF 1/8W 2% 10K	R4506	157333	2815583-728	RES CF 1/8W 2% 20K SJT200/300
R2017	157334	2815583-724	RES CF 1/8W 2% 13K	R4507	157377	2815583-711	RES CF 1/8W 2% 3.9K SJT200/300
R2019	829522	993218-477	RES CF 1/4W 5% 2.2M	R4508	829210	993218-697	RES CF 1/4W 2% 1K SJT200/300
R2020	143848	1479265-013	RES CONTROL 5V REF	R4509	157376	2815583-737	RES CF 1/8W 2% 47K SJT200/300
R2024	145384	993273-325	* RES CFFF 1/2W 5% 1.0R	R4510	829147	993218-689	RES CF 1/4W 2% 470R SJT200/300
R2025	829427	993272-335	* RES CFFF 1/4W 5% 2.7R			300	
R2504	829010	993113-177	* RES MFFF 1/4W 5% 10R	R4615	829147	993218-689	RES CF 1/4W 2% 470R SJT200/300
R2516	157335	2815583-722	RES CF 1/8W 2% 11K	R4616	829147	993218-689	RES CF 1/4W 2% 470R SJT200/300
R2704	829115	993113-205	* RES MFFF 1/4W 5% 150R				
R3101	829130	993218-684	RES CF 1/4W 2% 300R				
R3118	829010	993113-177	* RES MFFF 1/4W 5% 10R	R5126	829239	993218-711	RES CF 1/4W 2% 3.9K
R3129	829110	993113-201	* RES MFFF 1/4W 5% 100R	R5127	829047	993113-193	* RES MFFF 1/4W 5% 47R
R3131	151270	1479265-047	RES CONTROL DC BAL ADJ	R5138	829010	993117-177	* RES MFFF 1/4W 5% 10R
R3202	147615	1479265-020	RES CONTROL VIDEO LEVEL ADJ	R5139	829010	993113-177	* RES MFFF 1/4W 5% 10R
R3213	829010	993113-177	* RES MFFF 1/4W 5% 10R	R5156	829010	993218-349	RES CF 1/4W 5% 10R
R3221	157333	2815583-728	RES CF 1/8W 2% 20K	R5157	829010	993218-349	RES CF 1/4W 5% 10R
R3222	157333	2815583-728	RES CF 1/8W 2% 20K	R5309	829010	993113-177	* RES MFFF 1/4W 5% 10R
R3304	151270	1479265-047	RES CONTROL DELAY VIDEO ADJ	R5315	147040	993218-472	RES CF 1/4W 5% 1.3M
R3312	146175	1479265-019	RES CONTROL CHROMA LEVEL ADJ	R5917	830022	993290-185	* RES MFFF 1/2W 5% 22R
R3315	829133	993218-685	RES CF 1/4W 2% 330R	R5923	829110	993113-201	* RES MFFF 1/4W 5% 100R
R3316	829133	993218-685	RES CF 1/4W 2% 330R	R5932	145384	993273-325	* RES CFFF 1/2W 5% 1.0R
R3317	146175	1479265-019	RES CONTROL VERT DETAIL LEVEL ADJ	R5933	829110	993113-201	* RES MFFF 1/4W 5% 100R
R3322	829133	993218-685	RES CF 1/4W 2% 330R	R5943	145384	993273-325	* RES CFFF 1/2W 5% 1.0R
R3323	829133	993218-685	RES CF 1/4W 2% 330R	R5923	829110	993113-201	* RES MFFF 1/4W 5% 100R
R3324	829133	993218-685	RES CF 1/4W 2% 330R	R5956	145384	993273-325	* RES CFFF 1/2W 5% 1.0R
R3325	830113	993290-204	* RES MFFF 1/2W 5% 130R	S1	156527	2831429-004	* SWITCH POWER
R3326	829239	993218-711	RES CF 1/4W 2% 3.9K	S2	157639	1495451-026	* SWITCH AC OFF
R3327	829239	993218-711	RES CF 1/4W 2% 3.9K	S3	156527	2831429-004	* SWITCH POWER
R3328	143849	1479265-009	RES CONTROL LUMA CHANNEL ADJ	S4	157519	2860855-001	SWITCH CADDY SENSE
R3329	143849	1479265-009	RES CONTROL CHROMA CHANNEL ADJ	S5	157519	2860855-001	SWITCH SPINE SENSE
R3402	146175	1479265-019	RES CONTROL MOD DEPTH ADJ	S6	157519	2860855-001	SWITCH MECHANISM PLAY
R3404	157995	2815583-707	RES CF 1/8W 2% 2700R	S7	157519	2860855-001	SWITCH CADDY REVERSE
R3407	157339	2815583-704	RES CF 1/8W 2% 2K	S8	157519	2860855-001	SWITCH MECHANISM LOAD
R3408	157994	2815583-715	RES CF 1/8W 2% 5.6K	S10	157519	2860855-001	SWITCH LANDING
R3412	146175	1479265-019	RES CONTROL XC XD GAIN ADJ	S11	157519	2860855-001	SWITCH ARM HOME
R3418	147960	993272-341	* RES CFFF1/4W 5% 4.7R	S3501	158002	2816401-502	SWITCH CHANNEL SELECT
R3419	143848	1479265-013	RES CONTROL PHASE DET GAIN ADJ	S5601			
R3424	157340	2815583-469	RES CF 1/8W 5% 1M	S5607	157861	2861083-001	SWITCH FUNCTION MEMBRANE
R3438	147040	993218-472	RES CF 1/4W 5% 1.3M	T1	156300	2816285-001	* TRANSFORMER POWER
R3441	147040	993218-472	RES CF 1/4W 5% 1.3M				
R3442	147040	993218-472	RES CF 1/4W 5% 1.3M	U2001	149018	1421754-001	IC REF AMP/BUFFER/ERROR AMP
R3443	829322	993218-729	RES CF 1/4W 2% 22K	U2501	149019	1465648-001	IC SYNC DETECTOR
R3446	829022	993113-185	* RES MFFF 1/4W 5% 22R	U3101	149019	1465648-001	IC SYNC DETECTOR
R3449	829033	993113-189	* RES MFFF 1/4W 5% 33R	U3201	149036	1421760-001	IC VIDEO FM DEMODULATOR
R3452	157340	2815583-469	RES CF 1/8W 5% 1M	U3301	149039	1421752-001	IC COMB FILTER/DEFECT
R3464	829110	993113-201	* RES MFFF 1/4W 5% 100R	U3401	149018	1421754-001	IC ARM STRETCHER DRIVE/
R3509	829068	993113-197	* RES MFFF 1/4W 5% 68R	U3402	149034	1421761-001	IC VIDEO CONVERTER
R3510	829068	993113-197	* RES MFFF 1/4W 5% 68R	U3501	149037	1421758-001	IC RF MODULATOR
R3511	829310	993218-721	RES CF 1/4W 2% 10K	U3501	149037	1421758-001	IC RF MODULATOR
R3514	157993	2815583-690	RES CF 1/8W 2% 510R	U3402	149034	1421761-001	IC VIDEO CONVERTER
R3515	829247	993218-713	RES CF 1/4W 2% 4700R	U4101	149035	1421760-002	IC AUDIO DEMODULATOR L+R
R3516	157993	2815583-690	RES CF 1/8W 2% 510R	U4102	149035	1421760-002	IC AUDIO DEMODULATOR L-R
R3522	829547	993218-485	RES CF 1/4W 5% 4.7M				
R3524	829130	993218-684	RES CF 1/4W 2% 300R				
R3529	829239	993218-711	RES CF 1/4W 2% 3.9K	U4200	154027	1421710-002	IC TRACK/HOLD MUTE
R3531	829115	993218-677	RES CF 1/4W 2% 150R	U4300	149018	1421754-001	IC AUDIO MATRIX & BUFFER
R3532	829010	993218-349	RES CF 1/4W 5% 10R				
R4111	151270	1479265-047	RES CONTROL 716KHZ VCO FREQ ADJ	U4400	153405	1421754-002	IC DECODER RECTIFIER SJT200/300
R4112	151270	1479265-047	RES CONTROL 905KHZ VCO FREQ	U4500	149018	1421754-001	IC DECODER CONTROL SJT200/300
R4127	151371	1479265-049	RES CONTROL L+R LEVEL ADJ	U4600	153406	1421769-001	IC DECODER AMPLIFIER SJT200/300
R4127	151371	1479265-049	RES CONTROL L-R LEVEL ADJ	U5101	155884	1421786-002	IC PLAYER CONTROL
R4140	829010	993113-177	* RES MFFF 1/4W 5% 10R	U5101	155883	1421786-001	MICROCOMPUTER SJT100/200
R4141	829010	993113-177	* RES MFFF 1/4W 5% 10R				
R4203	829522	993218-477	RES CF 1/4W 5% 2.2M				

REPLACEMENT PARTS

Replacement Parts Continued (See Product Safety Note on first page of this parts list)

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION	SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION				
L901	148068	1445867-006	COIL 55MH	Q1001	142686	1417346-001	TRANSISTOR CRK34D				
Q901	148070	1417411-001	TRANSISTOR	Q1002	148061	1417333-002	TRANSISTOR CRK34C				
Q902	145410	1417330-011	TRANSISTOR	Q1002	142686	1417346-001	TRANSISTOR CRK34D				
Q903	148061	1417333-002	TRANSISTOR	Q1003	145395	1417318-007	TRANSISTOR CRK34D				
R919	155086	1468990-001	RES NETWORK	Q1003	153343	1417318-008	R TRANSISTOR CRK34C				
	133319	938316-013	GROMMET	T1001	153344	2860715-001	TRANSFORMER				
REMOTE AMPLIFIER											
PW1100	158004	2816405501	• CIRCUIT REMOTE AMP	155119	1497019-001	2816991-001	BATTERY, 1.5V AA				
C1101	146256	2841274-143	CAP LYTC 10UF M 25V	155118	1497000-001	1497019-001	BUTTON, DUAL				
C1102	145316	2841252-33H	CAPCD 56PF J N750 50V	153339	2843202-501	1497000-001	BUTTON, SINGLE				
C1103	139444	2871335-075	CAP POLY .1UF K 100V	158038	2831260-011	1497000-001	CASE, BOTTOM W/LENS				
C1104	149161	2841274-242	CAP LYTC 15UF N 25V	158012	2831260-012	1497000-001	CASE, TOP CRK34C				
C1105	155097	2871335-001	CAP POLY 1000PF M 100V	158017	2842241-512	1497017-001	CIRCUIT, SWITCH CONTACT				
C1106	155097	2871335-001	CAP POLY 1000PF M 100V	153346	1497017-001	1497017-001	CONTACT, DUAL BATTERY				
C1107	143882	2841255-30M	CAPCD .01UF Z Z5P 50V	153347	1497018-001	1497018-001	CONTACT, SINGLE BATTERY				
C1108	134939	2841255-50R	CAPCD .047UF Z Z5V 50V	153340	2831268-001	1497018-001	DOOR, BATTERY CRK33C				
C1109	134939	2841255-50R	CAPCD .047UF Z Z5V 50V	157177	2831268-022	1497018-001	DOOR, BATTERY CRK33D				
CR1101	119597	1471872-006	DIODE	153348	2843210-001	1444961-001	PAD, ANTI SKID				
CR1103	119597	1471872-006	DIODE	129796	1444961-001	1444961-001	SPRING, BATTERY CONTACT				
STYLUS CARTRIDGE											
P1102	158021	2861623-004	CONNECTOR 4 PIN	154216	2816412-501	1444961-001	CARTRIDGE, VIDEO PICKUP				
Q1101	148061	1417333-002	TRANSISTOR	TOOLS & LUBES							
R1101	829110	993113-201	* RES MFFP 1/4W 5% 100R	149073	2812522-503	1444961-001	• CADDY, LESS DISC				
U1101	154488	1421785-001	IC	153394	2812522-503	1444961-001	DISC, STEREO ALIGNMENT				
U1102	154487	1421784-001	IC	156529	2811825-002	1444961-001	GAUGE, TURNTABLE HEIGHT				
Y1101	154489	1422271-003	CRYSTAL, 632KHZ	149053	2811825-002	1444961-001	LUBRICANT, OIL				
INCLUDED ACCESSORIES											
REMOTE TRANSMITTER											
CRK34C,D											
157164	1457636-503	‡ TRANSMITTER, REMOTE CRK34C EARLY VERSION	149247	2811870-001	151303	1444961-001	• LUBRICANT, RYKON				
157233	1457636-504	‡ TRANSMITTER, REMOTE CRK34D LATE VERSION	149053	2811825-002	149053	1444961-001	• TOOL, HEX 2.5MM				
C1001	155457	2813595-007	CAPCM 560PF J NPO 100V	AH011	2871056-001	1444961-001	ADAPTER, 75 OHM COAX TO 300 OHM				
C1002	143882	1491409-32M	CAPCD .01UF K Z5P 50V	AH018	2871464-001	1444961-001	TWIN LEAD OUTPUT				
C1003	145896	1491409-50R	CAPCD .047UF Z Z5V 50V	153938	2872677-001	1444961-001	ADAPTER, 75 to 300 OHM w/90 DEGREE				
CR1001	148056	2811593-001	DIODE	AH004	2873052-001	1444961-001	PUSH-ON COAX CONNECTOR				
CR1001	153342	2811593-002	DIODE LED	2816991-001	2816991-001	1444961-001	BATTERIES, 1.5V AA SJT300				
CR1002	148056	2811593-001	DIODE LED CRK34C	2817352-001	2817352-001	1444961-001	BOOK, INSTRUCTION SJT100				
CR1002	153342	2811593-002	DIODE LED CRK34D	2817351-001	2817351-001	1444961-001	BOOK, INSTRUCTION SJT200				
CR1003	148056	2811593-001	DIODE	2817353-002	2817353-002	1444961-001	BOOK, INSTRUCTION SJT300				
CR1004	119597	1471872-006	DIODE	153938	2872677-001	1444961-001	CABLE, STEREO SJT200/300				
P1001	154364	2831318-022	CONNECTOR W/CONTACTS	AH004	2873052-001	1444961-001	CABLE, RF				
PW1000	155277	1458786-502	CIRCUIT COMPLETE CRK34C	28177356-001	28177356-001	1444961-001	CARD, SIMPLIFIED INSTRUCTIONS SJT100				
PW1000	158018	1458786-504	CIRCUIT COMPLETE CRK34D	2817355-001	2817355-001	1444961-001	CARD, SIMPLIFIED INSTRUCTIONS SJT200				
Q1001	148061	1417333-002	TRANSISTOR CRK34C	2817357-001	2817357-001	1444961-001	CARD, SIMPLIFIED INSTRUCTIONS SJT300				
JK											



SelectaVision® VideoDisc System CED Addendum Service Data

FILE
1983
SJT 100/200/300
Addendum-1

Model SJT 090/
100/101/200/300

RCA Corporation
Consumer Electronics

Technical Publications
P.O. Box 1976 | Indianapolis, Indiana 46206

RCA Inc.

Technical Publications

5575 Royalmount Avenue | Town of Mount-Royal | Quebec, Canada H4P 1J8

Canada Stock Numbers:

Add prefix 62 to all stock numbers.

Purpose of This Addendum: Update Basic Service Data to cover latest product design and provide Troubleshooting Guides.

Filing instructions: File this addendum immediately in front of 1983 SJT 100/200/300 Basic Service Data.

SUMMARY OF ADDITIONS/CHANGES COVERED BY THIS ADDENDUM

Original Service Data Contents	Page(s)	Additions/Changes in this Addendum	Page(s)
Instrument Disassembly	16 & 21	Revised Procedure	2
Electrical Adjustments	24	Order of Adjustment	2
Waveforms	36	Waveform No. 35	2
Interconnect Wiring Diagram	39 & 40	Add Capacitor	2
Power Supply Schematic	50	Delete Capacitor	2
Schematic Diagrams	42 thru 47	Component Value Changes	2
Replacement Parts	64 thru 70	Stock No. Changes and Deletions	3
		Stylus Lifter Alignment	2
		Troubleshooting Guides	4 thru 12

Instrument Disassembly pgs. 16 & 21**Turntable Height Adjust Step 1 Should Read**

1. If gauge plunger remains on lowest step—raise turntable height by adjusting height adjust screw (Item 99, Fig. 47) clockwise.

Turntable Removal Step 1. Should Read

1. With cabinet top, receiver spindle assembly and guide rail bracket removed—use thumb to rotate mechanism drive 2nd reduction gear (Fig. 16) in a clockwise direction to place mechanism in "PLAY" mode while holding AC switch (S2) actuator (Item 47, Fig. 47) back out of the way. Immediately stop rotating mechanism 2nd reduction gear when Disc transfer Rod Coupler (Item 38, Fig. 47) activates "PLAY" Switch S7 (forwardmost switch mounted on plastic AC IN board mounting bracket beside mechanism function gear).

Caution Note Should Read

CAUTION: There is a thrust plate (Item 102, Fig. 47) used in the turntable bearing. Be sure that it is in place before replacing turntable. Do not turn player upside down during servicing without turntable in place, it could result in possible loss of the thrust plate.

Electrical Adjustments page 24

Order of adjustment Chroma level adjust and Vertical detail adjust—

The Vertical Detail Level Adjust (R3317) should be performed prior to performing the Chroma Level adjust (R3312), otherwise the chroma level adjust must be repeated.

Waveforms page 36

Waveform 35 is presented upside down.

Interconnect Wiring Diagram pages 39 & 40

Add capacitor C1 0.047 μ F across Function motor B3 top of page 40.

Power Supply Schematic page 50

Delete Capacitor C2004, 4700 pf at 5V reference adjust control R2020.

Schematic Component Value Changes and Deletions pages 42 thru 47

Page 42—C5304 change to 33 μ F 25V

C5305 delete

R5156 should be safety related

Page 45—C3117 change to 10 μ F 25V

C3118 change to 10 μ F 25V

C3121 change to 33 pf

C3122 change to 10 μ F 25V

Schematic Note upper right corner of page 44

Should read:


NOTE: Early (initial) production instruments did not use Q5908, Q5909, R5976 and R5977. Should a failure occur requiring replacement of transistor Q5901 (Forward Function Switch) or Q5903 (Reverse Function Switch), look for the presence or absence of Q5908 and Q5909. Then refer to the replacement parts list for correct stock number for Q5901 or Q5903.

STYLUS LIFTER ALIGNMENT

If stylus lifter has been removed the use of a Lifter Alignment Gauge (see replacement parts list for Stock No.) is required when replacing it in the arm assembly.

The replacement and alignment procedure is as follows:

1. Reinstall Lifter Actuator Assembly - do not replace Lifter Pivot Clips at this time, see illustration.
2. Install Lifter Alignment Gauge (in same manner as installing Stylus Cartridge), see illustration.
3. Replace Lifter Pivot Clips (one on each side of arm assembly) and check to assure stylus lifter operates freely, see illustration.
4. Remove Lifter Alignment Gauge and install Stylus Cartridge.



Stylus Lifter Alignment

REPLACEMENT PARTS

BEFORE REPLACING PARTS, READ THE FOLLOWING:

RCA-Approved Substitute Stock Numbers—Before ordering stock numbers in this parts list, look for an RCA-approved substitute stock number in the current *RCA Distributor & Special Products Price Schedule*. This will minimize your service time and avoid ordering parts you already have in stock.

See your **RCA Distributor for Replacement Parts and Accessories**.

Warranty Status of Assemblies and Parts—The warranty status of some assemblies and parts are indicated by one of the following Warranty Status Codes:

- Complete assembly not eligible for warranty exchange or replacement.
- + Eligible for warranty exchange for new or rebuilt unit.
- ‡ Complete assembly eligible for warranty replacement with new or rebuilt unit.

.....AVOID REPLACEMENT PART ERRORS.....

File supplements and addendums immediately upon receipt, and consult the parts lists in them before ordering parts.

NOTE: For complete coverage of all parts and assemblies used in instruments equipped with the chassis series to which this service data relates, consult the following publications.

All parts listed without a Warranty Status Code symbol are eligible for warranty replacement as discrete components.

Warranty replacement of cabinet parts requires prior approval of RCA.

Warranty Status and Specifications of assemblies and parts are subject to change without notice.

PRODUCT SAFETY NOTE—Components marked with a (*) have special characteristics important to safety. Before replacing any of these components, read carefully the **PRODUCT SAFETY NOTICE** in the Basic Service Data. Do not degrade the safety of the set through improper servicing. Although assemblies as a whole may not be marked with a (*), replacement of RCA assemblies with other assemblies not RCA approved may result in a safety hazard.

Canada Stock Numbers:

Add prefix 62 to all stock numbers.

● **Basic Service Data**—Chassis and tuning systems and most related parts and assemblies that do not differ from one model or model group to another.

● **Service Data Supplements**—Cabinet, auxiliary, and other parts and assemblies that differ from one model group to another.

● **Service Data Addendum**—Any parts additions, deletions, or other changes made after initial production.

Do not replace or order parts without first consulting any Addendum(s) that may have been issued since publication of this service data.

CHANGE TO READ:

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
------------	-----------	-------------	-------------

UNDER:

ELECTRICAL COMPONENTS

DELETE:

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
------------	-----------	-------------	-------------

C2004	143967	2841254-81M	CAPCD 4700PF M Z5P 50V
C3506	157201	2841253-23A	CAPCD 270PF J NPO 50V
C3507	157202	2841262-020	CAPCD 300PF J NPO 50V
C3509	157202	2841262-020	CAPCD 300PF J NPO 50V
C5131	147971	2841255-31M	CAPCD .01UF M Z5P 50V SJT300
C5306	143878	2841253-62M	CAPCD 560PF K Z5P 50V
L3503	157192	2873326-011	COIL 0.52UH
L3504	157192	2873326-011	COIL 0.52UH
R3514	157993	2815583-690	RES CF 1/8W 2% 510R
R3516	157993	2815583-690	RES CF 1/8W 2% 510R

NOW READS:

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
------------	-----------	-------------	-------------

Q5305	140129	1417327-004	TRANSISTOR KICK PULSE OUTPUT
Q5306	140130	1417328-003	TRANSISTOR KICK PULSE OUTPUT
Q5901	140129	1417327-004	TRANSISTOR REV FUNCTION SW (LATE PRODUCTION)
Q5903	140129	1417327-004	TRANSISTOR FWD FUNCTION SW (LATE PRODUCTION)
Q5921	140130	1417328-003	TRANSISTOR CURRENT SOURCE SW
Q5923	140129	1417327-004	TRANSISTOR TURNTABLE MOTOR DRIVER B
Q5931	140130	1417328-003	TRANSISTOR CURRENT SOURCE SW
Q5933	140129	1417327-004	TRANSISTOR TURNTABLE MOTOR DRIVER A
Q5941	140130	1417328-003	TRANSISTOR CURRENT SOURCE SWITCH
Q5943	140129	1417327-004	TRANSISTOR TURNTABLE MOTOR DRIVER B
Q5951	140130	1417328-003	TRANSISTOR CURRENT SOURCE SW
Q5953	140129	1417327-004	TRANSISTOR TURNTABLE MOTOR DRIVER C


NOW READS:

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
C3117	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C3118	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C3121	143864	2841251-33A	CAPCD 10PF J NPO 50V
C3122	134939	2841255-50R	CAPCD .047UF Z Z5V 50V
C5301	153925	2872860-125	CAP POLY 0.1UF K 50V
C5304	143550	2841274-543	CAP LYTC 47UF M Z5U
R2024	145384	993273-325	* RES CFFP 1/2W 5% 1.0R
R4127	151371	1479265-049	RES CONTROL L-R LEVEL ADJ. SJT 200/300


CHANGE TO READ:

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
C3117	146256	2841274-143	CAP LYTC 10UF M 25V
C3118	146256	2841274-143	CAP LYTC 10UF M 25V
C3121	146833	2841251-93H	CAPCD 33PF J N750 50V
C3122	146256	2841274-143	CAP LYTC 10UF M 25V
C5301	159640	2872860-225	CAP POLY 0.1UF J 50V
C5304	149204	2841274-442	CAP LYTC 33UF N 25V
R2024	830A10	2817720-325	RES CFFP 1/2W 5% 1R
R4128	151371	1479265-049	RES CONTROL L-R LEVEL ADJ. SJT 200/300

TROUBLESHOOTING GUIDE





TROUBLESHOOTING GUIDE




Improper Turntable Operation


TROUBLESHOOTING GUIDE



TROUBLESHOOTING GUIDE




Player Won't Turn Off




No Arm Drive

TROUBLESHOOTING GUIDE




Incorrect Feature Operation

TROUBLESHOOTING GUIDE




TROUBLESHOOTING GUIDE




TROUBLESHOOTING GUIDE

1. MSA—Measure Signal At
2. Use Segment 'F' of Stereo Test Disc



No/Incorrect Stereo Output

TROUBLESHOOTING GUIDE



No/Incorrect Stereo Outputs



FILE
1983

SJT 100/200/300
Addendum—2

SelectaVision® VideoDisc System CED Addendum Service Data

Model SJT 090/
100/101/200/300

RCA Corporation Consumer Electronics

Technical Publications
P.O. Box 1976 | Indianapolis, Indiana 46206

RCA Inc.
Technical Publications
5575 Royalmount Avenue | Town of Mount-Royal | Quebec, Canada H4P 1J8

Canada Stock Numbers:
Add prefix 62 to all stock numbers.

Purpose of This Addendum: Update Basic Service Data to cover latest Replacement Parts List changes.

Filing Instructions: File this addendum immediately in front of 1983 SJT 100/200/300 Basic Service Data Addendum—1.

SUMMARY OF ADDITIONS/CHANGES COVERED BY THIS ADDENDUM

Original Service Data Contents	Page(s)	Additions/Changes In This Addendum	Page(s)
Schematic	43	Item Number Change	1
Replacement Parts	Basic Data 64 thru 77	Replacement Parts List Changes/Additions	2
	Addendum—1		

NOTE: Schematic on page 43 of Basic Service Data incorrectly shows Daxi Buffer IC as U5012—Should read U5102.

This is an Addendum Service Data. It covers model-related information and any exceptions to the Basic and/or Supplement Service Data 1983 SJT 100/200/300

BEFORE REPLACING PARTS, READ THE FOLLOWING:

RCA-Approved Substitute Stock Numbers—Before ordering stock numbers in this parts list, look for an RCA-approved substitute stock number in the current *RCA Distributor & Special Products Price Schedule*. This will minimize your service time and avoid ordering parts you already have in stock.

See your RCA Distributor for Replacement Parts and Accessories.

Warranty Status of Assemblies and Parts—The warranty status of some assemblies and parts are indicated by one of the following Warranty Status Codes:

- Complete assembly not eligible for warranty exchange or replacement.
- + Eligible for warranty exchange for new or rebuilt unit.
- # Complete assembly eligible for warranty replacement with new or rebuilt unit.

.....AVOID REPLACEMENT PART ERRORS.....

File supplements and addendums immediately upon receipt, and consult the parts lists in them before ordering parts.

NOTE: For complete coverage of all parts and assemblies used in instruments equipped with the chassis series to which this service data relates, consult the following publications.

All parts listed without a Warranty Status Code symbol are eligible for warranty replacement as discrete components.

Warranty replacement of cabinet parts requires prior approval of RCA.

Warranty Status and Specifications of assemblies and parts are subject to change without notice.

PRODUCT SAFETY NOTE—Components marked with a (*) have special characteristics important to safety. Before replacing any of these components, read carefully the **PRODUCT SAFETY NOTICE** in the Basic Service Data. Do not degrade the safety of the set through improper servicing. Although assemblies as a whole may not be marked with a (*), replacement of RCA assemblies with other assemblies not RCA approved may result in a safety hazard.

Canada Stock Numbers:

Add prefix 62 to all stock numbers.

● **Basic Service Data**—Chassis and tuning systems and most related parts and assemblies that do not differ from one model or model group to another.

● **Service Data Supplements**—Cabinet, auxiliary, and other parts and assemblies that differ from one model group to another.

● **Service Data Addendum**—Any parts additions, deletions, or other changes made after initial production.

Do not replace or order parts without first consulting any Addendum(s) that may have been issued since publication of this service data.

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
UNDER:			
ELECTRICAL COMPONENTS			
CHANGE TO READ:			
C5304	143550	2841274-543	CAP LYTIC 47μF M 25V
Q5901	160694	1417327-6	TRANSISTOR REV FUNCTION SWITCH (LATE PRODUCTION)
R5917	161710	2818520-48	RES FUSE 1/2W 5% 22R
J4602	157181	2816401-503	JACK AUDIO W/BRACKET SJT 200/300
ADD:			
FL4101	160168	2861062-001	FILTER
FL4102	160169	2861062-002	FILTER
FL4103	160170	2861062-003	FILTER
FL4104	160171	2861062-004	FILTER SJT 200/300
FL4105	160172	2861062-005	FILTER SJT 200/300
FL4106	160173	2861062-006	FILTER SJT 200/300

SYMBOL NO.	STOCK NO.	DRAWING NO.	DESCRIPTION
P14	158679	2861623-008	CONNECTOR 8 PIN SJT 100
P14	158674	2861623-009	CONNECTOR 9 PIN SJT 200/300
R5308	160542	2815583-747	RES CF 1/8W 2% 120K
UNDER:			
MECHANICAL ASSEMBLY			
CHANGE TO READ:			
7	159645	2861019-003	BUTTON, POWER